



Date:	3/11/09	MSDS No:	
Supersedes:			
Trade Name:			
Sizes:	All		

# MATERIAL SAFETY DATA SHEET

## SECTION I - IDENTIFICATION

<b>Manufacturer/Supplier:</b> Dial Manufacturing, Inc. 25 S. 51st Avenue Phoenix, Arizona 85043 Tel. No.: (602) 278-1100	<b>Product Name:</b>	COOLER COVER
	<b>Product Type:</b>	Finishing Treatment Used On Canvas Cooler Covers
	<b>Product Number(s):</b>	8301 thru 8648

## SECTION II – HAZARDOUS MATERIALS

Canvak Coating is a mixture of chemicals, the identities of which are being withheld pursuant to the trade secret exemption set forth at 29 C.F.R. Sections 1910.1200(g)(2)(i) and (l)(1)(i)

## SECTION III – PHYSICAL DATA

<b>Boiling Point:</b>	N/A	<b>Appearance and Odor:</b>	Waxy solid, slight odor
<b>Vapor Pressure (mm Hg):</b>	N/A	<b>Specific Gravity (H<sub>2</sub>O=1)</b>	55%
<b>Vapor Density (Air=):</b>	(Butyl Acetate = 1)	<b>Melting Point:</b>	120° F
<b>Solubility in Water:</b>	Material is insoluble	<b>Evaporation Rate:</b>	N/A

## SECTION IV – FIRE AND EXPLOSTION HAZARD DATA

<b>Flash Point:</b>	N/A	<b>Flammable Limits:</b>	N/A
<b>Extinguishing Media:</b>	Water or any media suitable for source.	<b>Evaporation Rate:</b>	N/A
<b>Special Fire Fighting Procedures:</b>	Self-contained breathing equipment	<b>Unusual Fire and Explosion Hazards:</b>	N/A

## SECTION V – REACTIVITY DATA

<b>Stability:</b>	Material is Stable
<b>Incompatibility (materials to avoid):</b>	Strong Acids
<b>Hazardous Decomposition or Byproducts:</b>	None
<b>Hazardous Polymerization:</b>	Will not occur

## SECTION VI – HEALTH HAZARD DATA

### Individual Components of Canvak Coating

Health hazards/signs and symptoms of exposure

<b>Eye:</b>	<u>Acute</u> – Exposure to fumes of two components of coating may cause temporary eye irritation. Contact with eyes by two components upon heating may produce eye burns.
<b>Skin:</b>	<u>Acute</u> – Exposure to two components of coating may cause skin irritation or reaction. Exposure to one component of coating may cause, in extreme cases, inflammation, cracking, and a possible secondary infection. Contact with skin by two components upon heating may produce skin burns.
<b>Inhalation:</b>	<u>Acute</u> – Inhalation of three components of coating may cause irritation of the respiratory tract. Excessive inhalation of one component may cause dizziness and central nervous system depression.
<b>Ingestion:</b>	<u>Acute</u> – Ingestion of three components of coating may cause harm, including gastrointestinal disturbances and intestinal obstruction.
<b>Carcinogenicity:</b>	Canvak contains no listed carcinogens to which downstream employees may be exposed.

## SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

<b>Steps to be taken in case material is released or spilled:</b>	If melted material is spilled, contain material, let cool and harden, then remove.
<b>Waste Disposal Method:</b>	Dispose in accordance with all local, state and federal regulations.
<b>Precautions to be taken in Handling and Storage:</b>	A good ventilation system and eye protection is strongly recommended during heating, melting, and handling of solid Canvak.
<b>Other Precautions:</b>	Thin protective gloves should be worn if dermatitis occurs.

SECTION VIII – CONTROLS MEASURES	
<b>Respiratory Protection:</b>	None
<b>Ventilation:</b>	Local exhaust is recommended.
<b>Protective Gloves:</b>	Recommended
<b>Eye Protection:</b>	Strongly recommended during heating and melting of sold Canvak.
<b>Work/Hygiene Practices:</b>	Good industrial hygiene practice is recommended.