| Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements. Identity (As Used on Label and List) PROPANE | U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072 Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate | | | | | | | |
|--|---|--------|----------------------------------|-----------------------------|--------------|--|--|--|
| | that. | | | | | | | |
| SECTION 1 Supplier's Name | Emergency | Telepł | none Number | | | | | |
| | 800 -628 -8810 | | | | | | | |
| Address Number, Street, City, State and ZIP Code | Telephone Number for Information 800 -628 -8810 | | | | | | | |
| | Date Prepared | | | | | | | |
| 301 Chestnut Street | June 14 , 200 | | | | | | | |
| East Longmeadow , MA 01028 | Signature of Preparer (Optional) | | | | | | | |
| SECTION II - Hazardous Ingredients / Identity Information | | | | | | | | |
| Hazardous Components Specific Chemical Identity, Common Name(s) | OSHA PE | L | ACGIH TLV | Other Limits Recommended | % (optional) | | | |
| PROPANE CAS #74-98-6 | 1000P | РМ | 1000PPM | NA | 100 | | | |
| NFPA HAZARD RATINGS | HMISRA | TING | | | | | | |
| Health -1 Flammability -4 Reactivity -0 | Health -1 Flammability -4 Reactivity -0 | | | | | | | |
| Note: When propane fuel is burned efficiently, the normal by-products of combustion are CO ₂ and H ₂ 0. Inefficient burning may add CO to the by-products of combustion. | | | | | | | | |
| SECTION III - Physical / Chemical Characteristics | | | | | | | | |
| | -44° F Specific Gravity (H ₂ 0 - 1) Liquid @ 60° F .51 | | | | | | | |
| Vapor Pressure (mm Hg) @ 100° F 1 | 97 psig | Melt | ting Point | N/A | | | | |
| Vapor Density (AIR=1) @ 1 ATM @ 60° F | 1.56 | | poration R ate /I Acetate -1) | N/A | | | | |
| Solubility in Water | | | | | | | | |
| Not Soluble | | | | | | | | |
| Appearance and Odor | | | | | | | | |
| Colorless - Rotten Egg Odor | | | | | | | | |
| SECTION IV - Fire and Explosion Hazard Data | | | | | | | | |
| Flash Point (Method Used) -156° F Closed Cup | Flammable L imits | | | LEL 2.1 | UEL 9.5 | | | |
| Extinguishing Media | | | | | | | | |
| Stop flow of gas or oxygen | | | | | | | | |
| Special Fire Fighting Procedures | | | | | | | | |
| Use water to cool tanks | | | | | | | | |
| Unusual Fire and Explosion Hazards Auto Ignition temp. 842° F Heavier than air (vapor density 1.5). May travel a considerable distance to a source of ignition and flashback. | | | | | | | | |
| SECTION V - Reactivity Data | aistance | 10 0 | source or ig | | | | | |
| Stabilit y → Unstable Conditions to Av | oid | - | | | | | | |
| Stable X | N/A | | | | | | | |
| Incompatibility (Materials to Avoid) N/A | | | | | | | | |
| Hazardous Decomposition or Byproducts None | | | | | | | | |
| HazardousMay OccurConditionsPolymerization →Will Not OccurX | to Avoid N/A | | | | | | | |

| SECTION VI - Health Hazard Data | | | | | | | | | |
|--|---------------------------------------|--------------------------------|-----------------------|-------------------|------------------------|--|--|--|--|
| Routes of Entry → | Inhalation? YES | 2 | | in? ES | Ingestion? NO | | | | |
| Health Hazards (Acute and Chronic) | | | | | | | | | |
| Contact with liquid propane may cause frost burns | | | | | | | | | |
| Carcinogenicity → | ntp? N/A | | | onographs? I/A | OSHA Regulated? N/A | | | | |
| Signs and Symptoms of Exposure High concentrations may cause headaches and drowsiness. | | | | | | | | | |
| Medical Conditions Generally Aggravated by Exposure N/A | | | | | | | | | |
| Emergency and First Aid Procedu | ires | | | | | | | | |
| Remove exposed person from contaminated area. | | | | | | | | | |
| Warning This fuel, and byproducts of combustion of this fuel, contain chemicals known to the State of California to cause cancer, birth defects, and other reproductive harm. | | | | | | | | | |
| SECTION VII - Precautions for Safe Handling and Use | | | | | | | | | |
| | | nng anu | Use | | | | | | |
| Steps to be Taken in Case Material is Released or Spilled Remove ignition sources and ventilate area. | | | | | | | | | |
| Waste Disposal Method Vent gas to atmosphere in flame free, spark free area outdoors. | | | | | | | | | |
| Precautions to be Taken in Handling and Storing | | | | | | | | | |
| Store at temperatures below 120° F in well ventilated, spark free, flame | | | | | | | | | |
| | free area. | | | | | | | | |
| Other Precautions None | | | | | | | | | |
| SECTION VIII - Control Measures | | | | | | | | | |
| Respiratory Protection (Specify Type) Not required with normal use. | | | | | | | | | |
| Ventilation \rightarrow | Local Exhaust N/A | Mechan | ical (General) N/A | Special N/A | Other N/A | | | | |
| Protective Gloves Not required | k | Eye Protection Not required | | | | | | | |
| Other Protective Clothing or Equipment Not required | | | | | | | | | |
| Work / Hygienic Practices N/A | | | | | | | | | |
| SECTION IX - Shipping Information | | | | | | | | | |
| WHMIS Classification: A - Con | | | Class: 2.1 | | | | | | |
| DOT | Proper Shipping Petroleum Gas, Lie | | | | UN. No. 1075 | | | | |