

PE150

### 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

**PRODUCT:** Solest 150

CHEMICAL NAME/FAMILY: POLYOL ESTER

**OTHER NAME:** Refrigerant Oil

**MANUFACTURER:** NATIONAL REFRIGERANTS, INC. **ADDRESS:** 11401 Roosevelt Boulevard Phila., Pa. 19154

**INFORMATION:** 800-262-0012 **EMERGENCY:** 800-424-9300 **DATE:** 4/2018 **PREPARER:** Matt Callahan

### 2. HAZARD IDENTIFICATION

**CLASSIFICATION:** This material has no known hazards under applicable laws. The product contains no known carcinogens.

**OTHER HAZARDS:** Prolonged contact may cause minor skin irritation.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTCAS#WEIGHTProprietary FormulationProprietaryProprietary

## **COMMON NAMES AND SYNONYMS:**

Refrigerant Oil

• The specific chemical identity and percentages are claimed as a trade secret

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention if irritation persists.

**SKIN CONTACT**: Upon contact with skin, wash exposed area with soap and water.

**INHALATION:** Product is not toxic by inhalation. If oil mist is inhaled, remove to fresh air and consult physician.

**INGESTION:** Do not induce vomiting. If conscious, give 2 glasses of water and consult physician. May cause nausea and diarrhea.

### 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Dry Chemical; CO2 Foam; Water Spray (fog)

Page 1 of 4 Solest 150



PE150

**SPECIAL FIREFIGHTING PROCEDURES:** Toxic fumes, gases or vapors may evolve on burning. Firefighters should use NIOSH/MNSA- approved self-contained breathing apparatus. Use water to cool fire-exposed containers. Use water carefully near exposed liquid to avoid frothing and splashing of hot liquid.

**UNUSUAL FIRE AND EXPLOSION HAZARDS: None** 

## 6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE OF RELEASE OR SPILL: Stop the source of the spill. Dike the spill area. Use absorbent materials to soak up fluid (i.e. sand, sawdust, commericially available materials). Wash the spill area with large amounts of water. Properly dispose of all materials. Use personal protective equipment such as gloves, goggles, and converalls to prevent skin conact during clean up.

## 7. HANDLING AND STORAGE

**PRECAUTIONS FOR STORAGE AND HANDLING:** Do not take internally. Avoid contact with skin, eyes, and clothing. Upon contact with skin, wash exposed area with soap and water. If product enters the eyes, flush with water for 15 minutes and consult a physician. Wash contaminated clothing before reuse. Keep container tightly sealed when not in use. Keep away from heat and flames.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **ENGINEERING CONTROLS**

Provide adequate ventilation when working in confined areas

## PERSONAL PROTECTIVE EQUIPMENT

**SKIN PROTECTION:** General work clothing and gloves (leather) should provide adequate protection. Any contaminated clothing should be promptly removed and washed before reuse.

**EYE PROTECTION:** For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles.

**RESPIRATORY PROTECTION:** None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, or release into confined space, where the concentration may be above the PEL use a NIOSH approved respirator.

<u>ADDITIONAL RECOMMENDATIONS</u>: Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn.

### **EXPOSURE LIMITS**

OSHA permissible concentration of mineral oil mist in air is 5 mg/m3.

Page 2 of 4 Solest 150



**PE150** 

## 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear to yellow liquid

ODOR: Mild , distinct
ODOR THRESHOLD: Not Determined
PH: Not Determined
MELTING/FREEZING POINT: Not Determined
BOILING POINT: >650 deg. F

FLASH POINT: 250 °C, 510.1 °F ASTM D 92 (Typical)

EVAPORATION RATE: Nil

FLAMMABILITY: Not applicable LEL/UEL: Not applicable

VAPOR PRESSURE: <0.01 mmHg @ 20 deg. C

VAPOR DENSITY: Not Determined

RELATIVE DENSITY:  $.95 (20 \, ^{\circ}\text{C}) \text{ Water} = 1.0$ 

SOLUBILITY: Negligible

PARTITION COEFFICIENT

n-Octanol/water:

AUTO IGNITION TEMPERATURE:

DECOMPOSITION TEMPERATURE:

Not Determined

Not Determined

Not Determined

## 10. STABILITY AND REACTIVITY

**STABILITY**: STABLE

**HAZARDOUS POLYMERIZATION:** Will not occur.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS:** Analogous compounds evolve carbon monoxide, carbon dioxide, and other unidentified chemicals when burned.

### 11. TOXICOLOGICAL INFORMATION

INHALATION AND SKIN ABSORPTION HEALTH RISKS: N/A

**SKIN AND EYE CONTACT:** Prolonged contact may cause minor skin irritation.

**SYMPTOMS OF EXPOSURE: N/A** 

**INGESTION:** N/A

**ACUTE AND CHRONIC HEALTH HAZARDS: N/A** 

Page 3 of 4 Solest 150



PE150

CARCINOGENICITY: NTP IARC

NO

IARC MONOGRAPHS

OSHA REGULATED

NO NO

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHOD:** Dispose of this product and all associated wasted in a licensed facility in accordance with appropriate Federal, State, and local regulations.

## 14. TRANSPORATION INFORMATION

US DOT ID NUMBER: None US DOT PROPER SHIPPING NAME: None US DOT HAZARD CLASS: None US DOT PACKING GROUP: None

## 15. REGULATORY INFORMATION

This material is not a hazardous waste under RCRA Regulation 40 CFR 261

## 16. OTHER INFORMATION

HMIS: H F R

0 1 0

### **DISCLAIMER:**

INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION. NO WARRANTY IS MADE CONCERNING THE ACCURACY AND NO LIABILITY SHALL BE MADE FOR CLAIMS FOR USE OR RELIANCE OF THE RECOMMENDATIONS CONTAINED HEREIN.

Page 4 of 4 Solest 150