ITW Permatex 10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex (877) 376-2839 Emergency: 800-255-3924 (ChemTel) International Emergency: 00+ 1+ 813-248-0585

# **Material Safety Data Sheet**

1. PRODUCT IDENTIFICATION		
Product Name:	MEDIUM STRENGTH THREADLOCKER BLUE 10 ML	
Item No:	24210	
Product Type:	Anaerobic	

2. COMPOSITION/INFORMATION ON INGREDIENTS				
Component	Weight%	ACGIH; TLV-TWA	OSHA PEL	
POLYGLYCOL DIMETHACRYLATE 25852-47-5	60-80	Not listed	Not listed	
POLYGLYCOL OLEATE 9004-96-0	20-40	Not listed	Not listed	
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<3	Not listed	Not listed	
TITANIUM DIOXIDE 13463-67-7	0.1-1.0	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>	

### 3. HAZARDS IDENTIFICATION

Toxicity:

May cause eye and skin irritation. Irritates mucous membranes. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. At elevated temperatures may cause irritation of the respiratory tract. May cause skin sensitization.

Primary Routes of Entry: Signs and Symptoms of Exposure: Eye and skin contact, ingestion, inhalation Repeated skin contact may cause allergic skin reactions. Skin redness. Ingestion may cause nausea and vomiting. Inhalation overexposure may cause irritation, coughing and flu-like symptoms. May cause pain, redness or swelling of the eyes and excessive blinking and tear production.

Component	Weight%	NTP	ACGIH Carcinogens	IARC Carcinogen
TITANIUM DIOXIDE	0.1-1.0	male rat-negative,	A4	Group 2B; Vol 93,2006; Vol
13463-67-7		female rat-negative,		47,1989
		male mice-negative,		
		female mice-negative		

**Aggravated Medical Condition:** 

Preexisting skin disorders.

4. FIRST AID MEASURES	
Ingestion:	If swallowed, do not induce vomiting - seek medical advice. Never give anything by mouth to an unconscious person.
Inhalation:	Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.
Skin Contact:	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Eye Contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.

## 5. FIRE FIGHTING MEASURES

Flash Point °F(C°):	>200°F (>93°C)
Recommended Extinguishing Media:	Carbon dioxide, Dry chemical, Foam
Special Fire-Fighting Procedures:	Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
Hazardous Products of Combustion:	Oxides of carbon
Unusual Fire/Explosion Hazards:	Closed containers may rupture or explode when exposed to extreme heat. May polymerize exothermically.
Lower Explosive Limit:	n/d

#### 5. FIRE FIGHTING MEASURES

Upper Explosive Limit:

n/d

### 6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE				
Storage:	Store away from water or moisture. Protect from contamination.			
Handling:	Avoid prolonged skin contact. Keep away from eyes. Wash hands before eating and smoking.			

8.	EXPOSURE	CONTROLS/PERSONAL PROTECTION
Eye	S:	Safety glasses.

Skin: Ventilation:

**Respiratory Protection:** 

#### N C

Neoprene or nitrile gloves recommended. General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Blue liquid
Odor:	Mild
Boiling Point:	>300°F
pH:	Does not apply
Solubility in Water:	Insoluble
Specific Gravity:	1.00-1.15
VOC(Wt.%):	<2%
Vapor Pressure:	n/d
Vapor Density (Air=1):	>1
Evaporation Rate:	n/d

### **10. STABILITY AND REACTIVITY**

Chemical Stability: Hazardous Polymerization: Incompatabilities:

Conditions to Avoid: Hazardous Products of Combustion: Stable at normal conditions May occur Strong oxidizers, free radical initiators, inert gases, Peroxides, Reducing agents Heat Oxides of carbon

#### 11. TOXICOLOGICAL INFORMATION

See Section 3

### 12. ECOLOGICAL INFORMATION

No data available

#### **13. DISPOSAL CONSIDERATIONS**

Recommended Method of Disposal:Disposal should be made in accordance with federal, state and local regulations.US EPA Waste Number:NH - Not a RCRA Hazardous Waste Material

## **14. TRANSPORTATION INFORMATION**

#### DOT (49CFR 172)

U.S. Department of Transportation - DOT	Γ - 49 CFR (Ground)

DOT Shipping Name:	Not regulated
Hazard Class:	None
UN/ID Number:	None
IATA (Air)	
Proper Shipping Name:	Not regulated
Class or Division:	None
UN/ID Number:	None

IMDG (Vessel)

Proper Shipping Name:	Not regulated
Hazard Class:	None
UN Number:	None

Marine Pollutant:

#### **15. REGULATORY INFORMATION**

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

#### DIMETHYLBENZYL HYDROPEROXIDE

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

#### **16. OTHER INFORMATION**

 Estimated NFPA Rating:
 HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

 Estimated HMIS Classification:
 HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

 (NFPA is a registered trademark of the National Fire Protection Association)
 HMIS is a registered trademark of the National Paint and Coatings Association)

None

Prepared By:	Denise Boyd, Manager-Environmental, Health & Safety	Revision Date: January 10, 2013
Company:	ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106	Revision Number: 7
Telephone No.:	1-87-Permatex (877) 376-2839	