

HEAT-SEAL Stik®

LA-CO Industries, Inc.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 10/01/2015
Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : HEAT-SEAL Stik®

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : sealant

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.
1201 Pratt Boulevard
Elk Grove Village, IL. 60007-5746
Phone: (847) 956-7600
Fax: (847) 956-9885
E-mail: customer_service@laco.com

1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Skin Irrit. 2 H315
Eye Irrit. 2A H319
Skin Sens. 1 H317
Repr. 2 H361
Aquatic Chronic 2 H411

Full text of classification categories and H statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

GHS08

GHS09

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) :
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H361 - Suspected of damaging fertility or the unborn child
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :
P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P261 - Avoid breathing dust, fume
P264 - Wash hands thoroughly after handling
P272 - Contaminated work clothing must not be allowed out of the workplace
P273 - Avoid release to the environment
P280 - Wear eye protection, protective gloves, protective clothing
P302+P352 - If on skin: Wash with plenty of water
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P321 - Specific treatment (see First aid measures on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse

HEAT-SEAL Stik®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

P363 - Wash contaminated clothing before reuse
P391 - Collect spillage
P405 - Store locked up
P501 - Dispose of contents/container to an authorised waste collection point

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% (w/w)	GHS-US classification
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)	(CAS No) 25068-38-6	75 - 100	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
4,4'-isopropylidenediphenol	(CAS No) 80-05-7	1 - 2.5	Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 STOT SE 3, H335

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Suspected of damaging fertility or the unborn child.

Symptoms/injuries after inhalation : Inhalation of vapours may cause respiratory irritation.

Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry chemical. Water spray. Foam.

Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Burning produces irritating, toxic and noxious fumes.

Explosion hazard : Product is not explosive.

Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

Firefighting instructions : Evacuate area. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. Do not breathe dust.

HEAT-SEAL Stik®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.
Emergency procedures : Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Avoid generating dust. Contain and collect as any solid.

6.4. Reference to other sections

Section 7: safe handling. Section 8: personal protective equipment. Section 13: disposal information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid breathing dust, fume. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.
Incompatible products : Strong oxidizers.
Heat and ignition sources : Keep away from heat, sparks and flame.
Prohibitions on mixed storage : Incompatible materials.
Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

sealant.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HEAT-SEAL Stik®	
ACGIH	Not applicable
OSHA	Not applicable
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	
ACGIH	Not applicable
OSHA	Not applicable
4,4'-isopropylidenediphenol (80-05-7)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls : Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Ensure good ventilation of the work station.
Personal protective equipment : Avoid all unnecessary exposure.
Hand protection : Wear suitable gloves.
Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing. Long sleeved protective clothing.
Respiratory protection : In case of inadequate ventilation wear respiratory protection. Use air-purifying respirator equipped with particulate filtering cartridges.
Other information : Do not eat, drink or smoke when using this product.

HEAT-SEAL Stik®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Green.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 450 °C
Auto-ignition temperature	: 450 - 600 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1.2 - 1.9
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and noxious fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg

4,4'-isopropylidenediphenol (80-05-7)

LD50 oral rat	> 2000 (2000 - 5000) mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	170 mg/m³ 6 h, no mortality observed

HEAT-SEAL Stik®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

4,4'-isopropylidenediphenol (80-05-7)

ATE CLP (oral)	2000.000 mg/kg bodyweight
ATE CLP (dermal)	3000.000 mg/kg bodyweight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated exposure)	: Not classified
---	------------------

Aspiration hazard	: Not classified
--------------------------	------------------

Potential adverse human health effects and symptoms

Symptoms/injuries after inhalation	: Inhalation of vapours may cause respiratory irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Likely routes of exposure	: Inhalation;Skin and eye contact

SECTION 12: Ecological information

12.1 Toxicity

Ecology - water	: Toxic to aquatic life with long lasting effects.
-----------------	--

reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

LC50 fish 1	4.4 mg/l 24 h
EC50 Daphnia 1	2.8 mg/l 48 h

4,4'-isopropylidenediphenol (80-05-7)

LC50 fish 1	9.4 mg/l 96 h
EC50 Daphnia 1	10.2 mg/l 48 h

12.2. Persistence and degradability

HEAT-SEAL Stik®

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

4,4'-isopropylidenediphenol (80-05-7)

Biodegradation	89 % 28 d
----------------	-----------

12.3. Bioaccumulative potential

reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

Log Pow	>= 2.918
Bioaccumulative potential	Not expected to bioaccumulate.

4,4'-isopropylidenediphenol (80-05-7)

Log Pow	3.4
---------	-----

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

HEAT-SEAL Stik®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 14: Transport information

In accordance with DOT and TDG

Transport document description	: UN3077 Environmentally hazardous substances, solid, n.o.s. (Epichlorhydrin Bisphenol A resin), 9, III
UN-No.(DOT)	: UN3077
Proper Shipping Name (DOT)	: Environmentally hazardous substances, solid, n.o.s. (Epichlorhydrin Bisphenol A resin)
Transport hazard class(es) (DOT)	: 9 - Class 9 (Miscellaneous dangerous materials)
Packing group (DOT)	: III - Minor Danger

ADR

Transport document description	: UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epichlorhydrin Bisphenol A resin), 9, III, (E)
Proper Shipping Name (ADR)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epichlorhydrin Bisphenol A resin)
Packing group (ADR)	: III
Transport hazard class(es) (ADR)	: 9

Transport by sea

UN-No. (IMDG)	: UN 3077
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epichlorhydrin Bisphenol A resin)
Transport hazard class(es) (IMDG)	: 9
Packing group (IMDG)	: III

Air transport

UN-No. (IATA)	: UN 3077
Proper Shipping Name (IATA)	: Environmentally hazardous substance, solid, n.o.s. (Epichlorhydrin Bisphenol A resin)
Transport hazard class(es) (IATA)	: 9
Packing group (IATA)	: III

SECTION 15: Regulatory information

15.1. US Federal regulations

reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4,4'-isopropylidenediphenol (80-05-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

4,4'-isopropylidenediphenol (80-05-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

4,4'-isopropylidenediphenol (80-05-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

HEAT-SEAL Stik®

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).

All ingredients are listed in the Toxic Substances Control Act (TSCA).

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

15.3. US State regulations

4,4'-isopropylidenediphenol (80-05-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New York - Right to Know List of Hazardous Chemicals


HEAT-SEAL Stik®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 16: Other information

Indication of changes	: Original Document.
Data sources	: ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html .
Abbreviations and acronyms	: ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number. CLP: Classification, Labelling, Packaging. EC50: Environmental Concentration associated with a response by 50% of the test population. GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). LD50: Lethal Dose for 50% of the test population. OSHA: Occupational Safety & Health Administration. PBT: Persistent, Bioaccumulative, Toxic. TWA: Time Weight Average. TSCA: Toxic Substances Control Act.
Other information	: None.
NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Full text of H-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H411	Toxic to aquatic life with long lasting effects

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

LACO NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product