Material Safety Data Sheet May be used to comply with

OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072 *Note: Blank spaces are not permitted. If any item is not applicable*

IDENTITY (As Used on Label and List)	CMD-10T, CMD-10T-A NA2319	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
Section I		

Manufacturer's Name	Emergency Telephone Number
Crow Marketing & Distribution Inc./Dist. by Golden Eagle	800-255-3924
Address <i>(Number, Street, City, State, and ZIP Code)</i>	Telephone Number for Information
P. O. Box 29171, Dallas, TX 75229	972-241-3049
	Date Prepared 06-14-94 REVIEWED 12/01/99
	Signature of Preparer (Optional)

Section II -- Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)	OSHA PEL	ACGIH TLV	Other Limits Recomended	% (optional)
No ingredients identified by OSHA as hazardous are known to be pres	ent, or the ingred	lients present are bel	ow levels specified as	hazardous by
OSHA (29 CFR 1910.1200).				50.0
Aliphatic Hydrocarbon CAS #5989-27-5	0	0		
Lauryl Dimethylamine Oxide CAS #1643-20-5				.5
Nonionic Alkoxylate CAS #N/A				5
Modified Coconut Diethanolamide CAS #111-42-2				9.5
Butyl Cellosolve CAS #111-76-2				10.0

			HMIS INFOR	MATION
			Health	1
			Flammability	1
			Reactivity	0
Section III Physical/Chemical Cha	Protection	0		
Boiling Point	348°F-176°C	Specific Gravity ($H_2O = 1$)	•	.843 @ 77°F
Vapor Pressure (mm Hg.)	1.00	Melting Point		N/A
Vapor Density (AIR = 1)	4.7	Evaporation Rate (Butyl Acetate = 1) Less than 1 Estimated slo		slower than ether.
Solubility in Water Negligible				
Appearance and Odor Clear liquid to slight yellow, citrus odor				
Section IV Fire and Explosion Ha	zard Data			
Flash Point (Method Used) Pensky-Martens Closed-Cup 130°		Flammable Limits 302°F	LEL 7%	UEL 6.1
Extinguishing Media Water Spray (not direct stream), all purpose for	oam. CO or dry chemica	al for small fires.		

Special Fire Fighting Procedures

Self-contained positive pressure breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. Treat as oil fire, Class B fire procedures, DO NOT USE WATER.

Unusual Fire and Explosion Hazards

Keep away from sparks, open flames, guard against spontaneous combustion of improperly discarded rags. Burning generates CO, CO₂ and smoke.

Section V -	Reactivity Data					
Stability	Unstable Conditions to Avoid					
	Stable	Х	None known			
Incompatiblity (Materials to Avoid)					
	ng Agents, Acidic Clay composition or Byprodu					
None known			-			
Hazardous Polymerization	May Occur		Conditions to Avoid Open flame			
,	Will Not Occur	X				
	Health Hazard	Data				
Route(s) of Ent	ry: Inhala Ye		Ski	1?	Ingestion? Yes	
Health Hazards	(Acute and Chronic)	5			105	
Carainaganiaitu	: NTP?		ΙΔR	C Monographs?	OSHA Regulated?	
Carcinogenicity	N/A			N/A	N/A	
Signs and Sym	ptoms of Exposure					
Medical Conditi		Nenel				
Generally Aggr	avated by Exposure	None	KNOWN.			
Emergency and	First Aid Procedures					
EYES: Flush (eyes immediately with				pious amounts of soap & water. Remove	
contaminated of physician imm		e re-use	e INGESTION: Do not induce	e vomiting. Rinse mouth w	ith water then drink a glass of water. Contac	:t
		r Safe	Handling and Use			
Steps to Be Tal	en in Case Material is	Release	ed or Spilled			
Soak up with a	bsorbant material, sho	ovel into	o waste container, flush area	with water.		
Waste Disposa						
Recover mater	ial or dispose in accor	dance	with all applicable Federal, S	tate, and local regulations	Absorb with rags, sand, or clay.	
Precautions to Avoid extreme	Be Taken in Handling a	nd Stori	ng			
	neat.					
Other Precautio						
Keep out of rea	ach of children. Comb	ustible				
Section VII	Control Measu	ires				
	tection (Specify Type)					
N/A Ventilation	Level Fullewet			Creation		
ventilation	Local Exhaust Recommended		ded	Special		
	Mechanical (General)			Other Use adequate ver	tilation	
Protective Glov			Eye	Eye Protection Wear full face shield or goggles when handling		
Use impervious gloves Other Protective Clothing or Equipment		VVez				
Wear protectiv	e clothing to prevent r	epeated	d or prolonged contact.			
Work/Hygienic	Practices					