### MATERIAL SAFETY DATA SHEET

Business Hours 8:00 am - 5:00 pm **Emergency Telephone Number** 972/442-6545

HARDCAST PRODUCTS CARLISLE COATINGS AND WATERPROOFING, INC.

Subsidiary of Carlisle Corporation 900 Hensley Lane Wylie, Texas 75098 FOR TRANSPORTATION EMERGENCIES CALL CHEMTREC 800/424-9300

	SECTION	1						
PRODUCT NAME & SYNONYMS	CHEMICAL FA	AMILY					HMIS RATINGS	
LAG GRIP 671	Synthe	ethic Resins				Н	IEALTH	1
PRODUCT USE	FORMULA					F	LAMMABILITY	0
Lagging Sealant		Mixture				F	REACTIVITY	0
	SECTION	IIA - HAZARDOU	S INGREDIENTS					
HAZARDOUS INGREDIENTS	CAS#	%	OSHA	PEL		LD50 o	f LC50 of	
			TWA	STEL	Ceiling	[ Ingredi	ent Ingredient	
Methanol	67-56-1	1-3	200ppm	250 ppm	None	oral-rat:	1 HL LCLo:	
						5628 mg/k	g 64,000	

	SECTION IIB - ADDITIONAL	INGREDIENTS (> 3%)	
Hydrocarbon Resins	CAS # Proprietary	Hydrated alumina	CAS # 21645-51-2
Water	CAS # 7732-18-5	P(BA/VAC)	CAS # 25067-01-0
Calcium Carbonate	CAS # 1317-65-3		N/E=Not established N/A=Not applicable
	SECTION III - PHYSICAL D	ATA	
SPECIFIC GRAVITY	BOILING POINT	% VOLATILES BY WT	VAPOR DENSITY (Air = 1)
1.22	212°F (100°C)	50%	Not Established
VAPOR PRESSURE	FREEZING POINT	SOLUBILITY IN WATER	EVAPORATION RATE
Not Established	32°F (0°C)	Appreciable	Not Established
рН	PHYSICAL STATE	ODOR THRESHOLD	voc
9.0 - 10.0	Viscous liquid	Not Established	118 gms/liter(water excluded)

ODOR & APPEARANCE

White liquid with acrylic odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY IF YES, UNDER WHAT CONDITIONS					
Not Flammable					
FLASHPOINT	AUTOIGNITION TEMPERATURE	LOWER FLAMMABLE LIMIT	UPPER FLAMMABLE LIMIT		
None	Not Applicable	Not Applicable	Not Applicable		

HAZARDOUS COMBUSTION PRODUCTS

Combustion may yield normal combustion byproducts: carbon dioxide, carbon monoxide, or nitrous oxides.

EXTINGUISHING MEDIA

None needed for liquid. For dry film, use water, foam, Carbon dioxide, or dry chemical

SPECIAL FIREFIGHTING PROCEDURES

Follow normal fire fighting procedures. Firefighters should wear self-contained breathing apparatus,

especially in enclosed areas. Cool drums and minimize vapor with water spray.

UNUSUAL FIRE & EXPLOSION HAZARDS

This product is not sensitive to physical shock or static discharge. Emulsion will not burn.

Exposure of closed container to temperatures above the boiling point could cause pressure buildup and container rupture. Dry mastic is capable of burning

Taptal of 21) made to capable of banning.				
SECTION V - REACTIVITY DATA				
This product is chemically stable.	CONDITIONS TO AVOID			
Hazardous polymerization will not occur.	Freezing or boiling.			
INCOMPATIBILITY				

Materials that react with water such as concentrated acids, calcium carbide, sodium.

Combustion may yield carbon dioxide, carbon monoxide, or nitrous oxides.

## **SECTION VI - TOXICOLOGICAL PROPERTIES**

EFFECTS OF ACUTE EXPOSURE TO PRODUCT

Due to concentration, ingestion, skin contact, or inhalation of sufficient quantities to induce symptoms unlikely.

Eye Contact: This material may cause eye irritation. Direct contact with liquid may cause stinging, tearing, redness.

Skin Contact: This material is not expected to be a skin irritant. Skin absorption is unlikely. If left on skin, a film will form. Based on method of removal, irritation may result.

Ingestion of sufficient quantities to induce symptoms unlikely.

Ingestion: Low degree of oral toxicity. Ingestion of excess quantities may cause irritation of GI tract.

PRODUCT NAME LG 671 Page 2

Inhalation of sufficient quantities to induce symptoms unlikely.

Inhalation: Breathing high concentrations of vapors may cause nausea & irritation of nose, throat, & respiratory tract.

Respiratory symptoms associated with preexisting lung disorders may be aggravated by exposure to this mat'l.

METHANOL: Toxic effects on CNS, headache, dizziness, intoxication, even death.

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT

N	JΩ	ne	kr	OV	vn

EXPOSURE LIMITS	SENSITIZATION TO PRODUCT	IRRITANCY OF PRODUCT	SYNERGISTIC PRODUCTS
None established	May cause skin sensitization	May irritate skin, eyes, and	None known
	in some individuals.	respiratory tract.	
CARCINOGENICITY	MUTAGENICITY & TUMORIGENICITY	REPRODUCTIVE TOXICITY	TERATOGENICITY
No evidence	No evidence	No evidence	No evidence

SECTION VII - PREVENTIVE MEASURES				
EYE PROTECTION	GLOVES			
Safety Glasses, Goggles, Face Shield recommended	Hycron, neoprene, or nitrile gloves recommended.			
RESPIRATOR	FOOTWEAR			
No special protection necessary	No special protection necessary			

Avoid unnecessary contact with this and any other chemical. Wash thoroughly after handling all chemicals.

No special protection necessary. Source of clean water should be available for flushing eyes and washing skin.

Use general and local exhaust as needed to maintain emissions below PEL.

No special control measures necessary under normal conditions of use.

LEAK OR SPILL PROCEDURE

Contain & remove with inert absorbent material.

Prevent spills, runoff, and washings from entering public sewers and open bodies of water.

Dispose of in accordance with all local, state, and federal regulations.

HANDLING PROCEDURES & EQUIPMENT

Normal use condition doesn't produce respirable Silica. However, sanding, grinding and burning might release respirable Silica.

Keep out of reach of children. Launder contaminated clothing.

Wash with soap and water after use, especially before eating or drinking.

Store in a cool, dry location away from heat. Keep containers tightly closed and store with adequate ventilation.

Do not pressurize, cut weld or grind the containers or empty containers which may contain residual product & vapors.

SPECIAL SHIPPING INFORMATION

Avoid freezing & subjecting this product to temperature extremes. Class 60 Item Number 4620 Sub 5

### SECTION VIII - FIRST AID MEASURES

Immediately flush with running water for at least 15 minutes. Get medical attention if irritation persists.

SKIN CONTACT

Wash exposed area with soap and water. Get medical attention is irritation persists.

INHALATION

Remove to fresh air. If symptoms persist, seek medical attention. If necessary, give artificial respiration.

Do not induce vomiting. Get medical attention.

Immediately flush with running water for at least 15 minutes. Get medical attention if irritation persists.

Wash exposed area with soap and water. Get medical attention is irritation persists.

Remove to fresh air. If symptoms persist, seek medical attention. If necessary, give artificial respiration.

Methanol

Do not induce vomiting. Get medical attention.

# **SECTION IX - SARA SECTION 313 SUPPLIER NOTIFICATION**

This product contains the following toxic chemicals subject to the reporting requirements of SARA 313 of the Emergency Planning & Community Right-to-Know Act of 1986 & of 40CFR 372.

1-3

CHEMICAL NAME	CAS#	%	
Methanol	67-56-1	1-3	
PA, FL, MA, MN,NJ:			
CHEMICAL NAME	CAS#	%	

## 67-56-1 CANADA: WHIMS Class D Div 1B; Class D Div 2B; Class B Div 2

Methanol 67-56-1 1-3

	SECTION X - PREPARATION IN	NFORMATION	
PREPARED BY	DATE	REVISION#	SUPERSEDES ALL PREVIOUS
R & D Group	6 June 2002	#14	PUBLICATIONS

#### NOTICE

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Hardcast. The data on this sheet relates only to the specific material designated herein. Hardcast assumes no legal responsibility for use or reliance upon these data.