# **Material Safety Data Sheet**





Revision Number: 002.1

1. PRODUCT AND COMPANY IDENTIFICATION

**IDH number:** 

Item number:

Contact information:

Telephone: 860.571.5100

Internet: www.henkelna.com

Emergency telephone: 860.571.5100

231562

United States

22355

Product name: Product type: **ODC-Free Cleaner & Degreaser** Solvent based cleaner

**Company address:** Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

# 2. HAZARDS IDENTIFICATION

Region:

	EMER	GENCY OVERVIEW		
Physical state: Color: Odor:	Liquid Colorless citrus-fruit-like	HMIS: HEALTH: FLAMMABILITY: PHYSICAL HAZARD: Personal Protection:	2 2 0 See MSDS Section 8	
WARNING:	MAY CAUSE EY MAY BE HARM	CONTENTS UNDER PRESSURE. MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. COMBUSTIBLE LIQUID AND VAPOR.		
Relevant routes of exposur	e: Skin, Inhalatio	n, Eyes, Ingestion		
Potential Health Effects				
Inhalation:	concentrations concentrations	ations of vapors may cause harmful effects. S above the recommended exposure limits. Sy exceeding the recommended exposure limits ss. Headache. Nausea.	mptoms are typically seen at air	
Skin contact:	May cause irrit	May cause irritation due to defatting of the skin. Prolonged contact with skin may cause dermatitis. May be harmful if absorbed through skin.		
Eye contact: Ingestion:	Direct spray or Ingestion caus	vapors will irritate and may harm eyes. es irritation and effects similar to inhalation. If Iting in inflammation and possible fluid accum		
Existing conditions aggrava exposure:	ated by Other pre-exist bronchial hype	ting skin conditions. Other respiratory disorder rreactivity).	rs (bronchitis, emphysema,	
	This material is 1910.1200).	s considered hazardous by the OSHA Hazard	Communication Standard (29 CFF	

See Section 11 for additional toxicological information.

Hazardous components	CAS NUMBER	%
Naphtha (petroleum), hydrotreated heavy Benzene < 0,1 %	64742-48-9	30 - 60
C13-14 Isoparaffin	64742-47-8	30 - 60
D-Limonene	5989-27-5	10 - 30
Carbon dioxide	124-38-9	5 - 10

3. COMPOSITION / INFORMATION ON INGREDIENTS

4	. FIRST AID MEASURES
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Wash with soap and water. Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
5. F	FIRE FIGHTING MEASURES
Flash point:	88 °C (190.4 °F)
Flashback:	This product exhibits no flashback when tested for flame extension.
Flame projection:	91.00 cm (35.83 inch)
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	0.7 %
Flammable/Explosive limits - upper:	5 %
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Fire fighters should wear positive pressure self-contained breathing apparatu (SCBA). Water may be unsuitable as an extinguishing media, but may be helpful in keeping adjacent containers cool. Avoid spreading liquid with water used for cooling purposes.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Spilled liquid is combustible and can be ignited by heat, flames, sparks, or other sources of ignition. Vapors are heavier than air and may travel along the ground or be moved by ventilation and subsequently ignited by heat, pilot lights or other ignition sources at locations distant from the material handling point. Remove all sources of ignition. Maintain good ventilation for large spills. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Spilled material will solidify.
	point. Remove all sources of ignition. Maintain good ventilation for large spills Evacuate and ventilate spill area; dike spill to prevent entry into water system

# 7. HANDLING AND STORAGE

Handling:

Keep container closed. Do not puncture or incinerate pressurized containers. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Wash thoroughly after handling. Do not wear contact lenses. Keep out of the reach of children. Vapors will accumulate readily and may ignite explosively. Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Naphtha (petroleum), hydrotreated heavy Benzene < 0,1 %	None	None	None	196 ppm TWA
C13-14 Isoparaffin	None	None	None	None
D-Limonene	None	None	30 ppm (165.5 mg/m3) TWA	None
Carbon dioxide	5,000 ppm TWA 30,000 ppm STEL	5,000 ppm (9,000 mg/m3) TWA	None	None
Engineering controls:	sufficient to co limits. Provide	ventilation is recomme ntrol airborne contamii local ventilation for pro tilation, wear suitable	nation below occupation below occupation below occupation of the second se	onal exposure ned area. In case of
Respiratory protection:	Use NIOSH ap limit(s).	proved respirator if the	ere is potential to exc	eed exposure
Eye/face protection:	Safety goggles	or safety glasses with	n side shields.	
Skin protection:	Permeation res	sistant gloves (butyl ru	bber, nitrile rubber, p	olyvinyl alcohol).
9. PHYSIC	AL AND CHEM		<b>FIES</b>	
Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Specific gravity: Vapor density: Flash point: Flash point: Flashback: Flame projection: Flammable/Explosive limits - lower: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content:	> 300 °F (> 14 Not available 0.7718 0.7718 Heavier than a 88 °C (190.4 °f	<sup>=</sup> ) <hibits flashback="" no="" th="" wl<=""><th>: (&gt; 298.4 °F)</th><th>extension.</th></hibits>	: (> 298.4 °F)	extension.

#### **10. STABILITY AND REACTIVITY**

Stability:

Stable

Hydrocarbons.

Hazardous reactions:

Will not occur.

Hazardous decomposition products:

Incompatible materials:

Conditions to avoid:

Heat, flames, sparks and other sources of ignition. Fire or intense heat may cause violent rupture of packages.

# **11. TOXICOLOGICAL INFORMATION**

Strong oxidizing agents. Acids and bases.

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Naphtha (petroleum), hydrotreated heavy Benzene < 0,1 %	No	No	No
C13-14 Isoparaffin	No	No	No
D-Limonene	No	No	No
Carbon dioxide	No	No	No
Hazardous components		Health Effects/Target	Organs
Naphtha (petroleum), hydrotreated heavy Be	nzene < 0,1	Irritant	

## **12. ECOLOGICAL INFORMATION**

**Ecological information:** 

C13-14 Isoparaffin

D-Limonene

Carbon dioxide

Not available

## **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

D001: Ignitable.

Recommended method of disposal:

Hazardous waste number:

Follow all local, state, federal and provincial regulations for disposal.

Irritant

Irritant

Central nervous system

## **14. TRANSPORT INFORMATION**

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Hazard class or division: Identification number: Packing group: Marine pollutant:

Aerosols (Dipentene) 2.2 UN 1950 None Dipentene

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Hazard class or division: Identification number: Packing group:

Aerosols, non-flammable 2.2 UN 1950 None

<u>Water Transportation (IMO/IMDG)</u> Proper shipping name: Hazard class or division: Identification number: Packing group: Marine pollutant:

AEROSOLS (Dipentene) 2.2 UN 1950 None Dipentene

## **15. REGULATORY INFORMATION**

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.		
TSCA 12(b) Export Notification:	None above reporting de minimus		
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimus Immediate Health, Pressure, Fire None above reporting de minimus		
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.		
Canada Regulatory Information			
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.		
WHMIS hazard class:	A, B.3, D.2.B		
16. OTHER INFORMATION			

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format., Corrected information in Section(s): 2,14

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.