

Revision Number: 002.2

Issue date: 11/05/2012

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name: Product type:

FORM-A-THREAD 4.8ML SYR ACT Sealant

Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067 Item number: 28654_390222 Region: United States Contact information: Telephone: 860.571.5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT ENERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

701947

2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW				
Physical state: Liquid HEALTH: *2					
Color:		⊥iquid Gray	FLAMMABILITY:	*2	
Odor:		Sharp, Irri		1	
• • • • •		onaip, ini	Personal Protection:	See MSDS Section 8	
١	WARNING:	CA	AUSES EYE AND SKIN IRRITATION.		
		M	AY BE HARMFUL IF SWALLOWED OR INHALED.		
		M	AY CAUSE ALLERGIC SKIN REACTION.		
		M	AY CAUSE RESPIRATORY TRACT IRRITATION.		
Relevant routes of exposure:			Skin, Inhalation, Eyes		
Potential I	Health Effects				
Inhalation:			May cause irritation to nose and throat.		
Skin contact:			Causes skin irritation. May cause allergic skin reaction.		
Eye contact:			Vapors may irritate eyes. Contact with eyes will cause irritation. May be harmful if swallowed. May cause gastrointestinal tract irritation if swallowed.		
	Ingestion:		May be harmun il swallowed. May cause gastionitestinal tracti	initation il swallowed.	
Existing conditions aggravated by exposure:		ted by	Skin disorders. Eye disorders. Acrylic acid: Respiratory disorde	ers. Lung disease.	
			This material is considered hazardous by the OSHA Hazard Co 1910.1200).	ommunication Standard (29 CFR	

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	24448-20-2	60 - 100
Aluminum	7429-90-5	30 - 60
Silicon dioxide	7631-86-9	1 - 5
Tetrahydrofurfuryl methacrylate	2455-24-5	1 - 5

4. FIRST AID MEASURES

Inhalation:

Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact:	Remove contaminated clothing and footwear. Wash clothing before reuse. If symptoms develop and persist, get medical attention. Wash with soap and water.
Eye contact:	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.
Ingestion:	Do not induce vomiting. Keep individual calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	> 93 °C (> 199.4 °F) Tagliabue closed cup
Autoignition temperature:	Not available.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Oxides of aluminum. Irritating organic vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Clean-up methods:

Do not allow product to enter sewer or waterways.

Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:

Storage:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.
For safe storage, store at or below 38 °C (100.4 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	None	None	None	None
Aluminum	1 mg/m3 TWA Respirable fraction.	5 mg/m3 TWA (as Al) Respirable dust. 15 mg/m3 TWA (as Al) Total dust.	None	None
Silicon dioxide	6 mg/m3 TWA	20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
Tetrahydrofurfuryl methacrylate	None	None	None	None

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Engineering controls:

Use NIOSH approved respirator if there is potential to exceed exposure ${\sf limit}(s).$

Eye/face protection:

Skin protection:

Safety goggles or safety glasses with side shields.

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): **VOC content:**

Liquid Gray Sharp, Irritating Not available. Not applicable < 5 mm hg (27 °C (80.6 °F)) > 149 °C (> 300.2 °F) Not available. 1.57 Not available. > 93 °C (> 199.4 °F) Tagliabue closed cup Not available. Not available. Not available. Not available. Slight Not available. 3.6 %

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of aluminum. Irritating organic vapours.
Incompatible materials:	Strong oxidizing agents. Reducing agents. Acids. Bases. Rust. Zinc. Aluminum. Iron. copper Alkalis. Aldehydes. Amines. Free radical initiators. Peroxides.
Conditions to avoid:	Exposure to sunlight. Heat, flames, sparks and other sources of ignition. See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity:

Acute dermal product toxicity:

LD50 (rat) > 5,000 mg/kg (Estimated)

LD50 (rabbit) > 2,000 mg/kg (Estimated)

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
2-Propenoic acid, 2-methyl-, (1- methylethylidene)	No	No	No
Aluminum	No	No	No
Silicon dioxide	No	No	No
Tetrahydrofurfuryl methacrylate	No	No	No

Hazardous components	Health Effects/Target Organs
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	Irritant, Allergen
Aluminum	Central nervous system, Irritant, Lung
Silicon dioxide	Nuisance dust
Tetrahydrofurfuryl methacrylate	Irritant, Allergen

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Not a RCRA hazardous waste.

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR) Proper shipping name: Not regulated

Proper shipping name: Hazard class or division: Identification number: Packing group:

International Air Transportation (ICAO/IATA) Proper shipping name:

None Not regulated None None

None

None

None

Water Transportation (IMO/IMDG)

Packing group:

Hazard class or division:

Identification number:

Proper shipping name: Hazard class or division: Identification number: Packing group:

Not regulated None None None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification:	None above reporting de minimus
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimis Immediate Health, Delayed Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Aluminum (CAS# 7429-90-5).

California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List
WHMIS hazard class:	D.2.B
	16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 1,9

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.