# **Material Safety Data Sheet**





Revision Number: 005.2 Issue date: 11/19/2012

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: 50ML GASKET ELIMINATOR 510

Product type: Anaerobic Sealant

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 135474 Item number: 51031 Region: United States

Contact information: Telephone: 860.571.5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

 Physical state:
 Gel
 HEALTH:
 \*3

 Color:
 Pink
 FLAMMABILITY:
 1

 Odor:
 Mild
 PHYSICAL HAZARD:
 1

Personal Protection: See MSDS Section 8

WARNING: HARMFUL IF INHALED.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

CAUSES EYE IRRITATION.

Relevant routes of exposure: Lungs, Eyes, Skin

**Potential Health Effects** 

**Inhalation:** May be toxic if inhaled. May cause respiratory tract irritation.

Skin contact:May cause allergic skin reaction.Eye contact:Contact with eyes will cause irritation.Ingestion:Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polyglycol dimethacrylate	25852-47-5	30 - 60
Bisphenol A fumarate resin	39382-25-7	10 - 30
Adipic acid polymer with neopentylglycol, 1,4-butanediol and isononanol	208945-12-4	10 - 30
1,1'-(methylenedi-p-phenylene)bismaleimide	13676-54-5	5 - 10
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Saccharin	81-07-2	1 - 5
Cumene hydroperoxide	80-15-9	1 - 5
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1
Cumene	98-82-8	0.1 - 1

#### 4. FIRST AID MEASURES

Inhalation: If symptoms develop and persist, get medical attention. Move to fresh air.

Skin contact: Wash with soap and water. If symptoms develop and persist, get medical

attention. Remove contaminated clothing and footwear. Wash clothing before

reuse.

**Eye contact:** Get medical attention. Flush with copious amounts of water, preferably,

lukewarm water for at least 15 minutes, holding eyelids open all the time.

Ingestion: Get medical attention. Do not induce vomiting. Keep individual calm.

## 5. FIRE FIGHTING MEASURES

Flash point: > 93.3 °C (> 199.94 °F)

Autoignition temperature: Not available.

Flammable/Explosive limits - lower: Not available.

Extinguishing media: Foam, dry chemical or carbon dioxide.

**Special firefighting procedures:**Wear self-contained breathing apparatus and full protective clothing, such as

Not available.

turn-out gear.

Unusual fire or explosion hazards: None

Flammable/Explosive limits - upper:

Hazardous combustion products: Oxides of sulfur. Oxides of nitrogen. Oxides of carbon. Irritating organic

vapours.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Store in a partly filled, closed container until disposal. Soak up with inert

absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust).

#### 7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation.

Storage: For safe storage, store between 0 °C (32°F) and 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Bisphenol A fumarate resin	None	None	None	None
Adipic acid polymer with neopentylglycol, 1,4-butanediol and isononanol	None	None	None	None
1,1'-(methylenedi-p-phenylene)bismaleimide	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Saccharin	None	None	None	None
Cumene hydroperoxide	None	None	(SKIN) 1 ppm (6 mg/m3) TWA	None
1-Acetyl-2-phenylhydrazine	None	None	None	None
Cumene	50 ppm TWA	50 ppm (245 mg/m3) TWA (SKIN)	None	None

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be

required if concentrations exceed occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

Skin protection: Natural rubber gloves. Use impermeable gloves and protective clothing as

necessary to prevent skin contact. Butyl rubber gloves. Neoprene gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Gel
Color: Pink
Odor: Mild

Odor threshold:Not available.pH:Not applicable

Vapor pressure:< 5 mm hg (80 °F (26.7 °C))Boiling point/range:< 300 °F (> 148.9 °C) None

Melting point/ range:
Specific gravity:
Vapor density:

Not available.
1.1784
Not available.

Flash point: > 93.3 °C (> 199.94 °F)

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not available.

Not available.

Not available.

0.77 %; 8.47 g/l

## 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Irritating organic vapours. Oxides of sulfur. Oxides of carbon. Oxides of

nitrogen.

**Incompatible materials:** Strong oxidizing agents.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

## 11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 10,000 mg/kg

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
Bisphenol A fumarate resin	No	No	No
Adipic acid polymer with neopentylglycol, 1,4-butanediol and isononanol	No	No	No
1,1'-(methylenedi-p- phenylene)bismaleimide	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Saccharin	No	No	No
Cumene hydroperoxide	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No
Cumene	No	Group 2B	No

Hazardous components	Health Effects/Target Organs		
Polyglycol dimethacrylate	Irritant, Allergen		
Bisphenol A fumarate resin	No Target Organs		
Adipic acid polymer with neopentylglycol, 1,4-butanediol and isononanol	No Records		
1,1'-(methylenedi-p-phenylene)bismaleimide	No Target Organs		
Silica, amorphous, fumed, crystal-free	Nuisance dust		
Saccharin	No Target Organs		
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen		
1-Acetyl-2-phenylhydrazine	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity		
Cumene	Central nervous system, Irritant, Lung		

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 135474

Product name: 50ML GASKET ELIMINATOR 510

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:**Not a RCRA hazardous waste.

#### 14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Diphenylmethane

Bismaleimide)

Hazard class or division:

Identification number: UN 3082 Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Diphenylmethane Bismaleimide)

Hazard class or division: 9
Identification number: UN 3082

Packing group:

Marine pollutant: Diphenylmethane Bismaleimide

#### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Delayed Health, Immediate Health

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Cumene hydroperoxide (CAS# 80-15-9).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

WHMIS hazard class:

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. D.1.A. D.2.A. D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 9

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.