# **Material Safety Data Sheet**





Revision Number: 006.2 Issue date: 11/19/2012

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE® 518™ GASKET

**ELIMINATOR ® FLANGE SEALANT** 

**Product type:** Anaerobic Adhesive

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

**IDH number:** 135481

Item number:51831Region:United States

Contact information: Telephone: 860.571.5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

 Physical state:
 Gel
 HEALTH:
 \*2

 Color:
 Red
 FLAMMABILITY:
 1

 Odor:
 Mild
 PHYSICAL HAZARD:
 1

Personal Protection: See MSDS Section 8

WARNING: CAUSES EYE AND SKIN IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

MAY BE HARMFUL IF SWALLOWED.

Relevant routes of exposure: Skin, Lungs, Eyes

**Potential Health Effects** 

**Inhalation:** May cause irritation to nose and throat.

**Skin contact:** May cause allergic skin reaction. Causes skin irritation. **Eye contact:** Vapors may irritate eyes. Contact with eyes will cause irritation.

**Ingestion:** May cause gastrointestinal tract irritation if swallowed.

Existing conditions aggravated by

exposure:

IDH number: 135481

Eye, skin, and respiratory disorders. Acrylic acid: Respiratory disorders. Lung disease.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous components                   | CAS NUMBER  | %        |  |
|--|-------------|----------|--|
| Polyurethane methacrylate resin        | Proprietary | 60 - 100 |  |
| Polyglycol dimethacrylate              | 25852-47-5  | 5 - 10   |  |
| Silica, amorphous, fumed, crystal-free | 112945-52-5 | 5 - 10   |  |
| Acrylic acid                           | 79-10-7     | 1 - 5    |  |
| Cumene hydroperoxide                   | 80-15-9     | 1 - 5    |  |
| Ethylene glycol                        | 107-21-1    | 1 - 5    |  |
| 1-Acetyl-2-phenylhydrazine             | 114-83-0    | 0.1 - 1  |  |
| Cumene                                 | 98-82-8     | 0.1 - 1  |  |

Product name: LOCTITE® 518™ GASKET ELIMINATOR ® FLANGE SEALANT

Page 1 of 6

# 4. FIRST AID MEASURES

Inhalation: If symptoms develop and persist, get medical attention. Move to fresh air.

Skin contact: Wash with soap and water. Remove contaminated clothing and footwear.

Wash clothing before reuse. If symptoms develop and persist, get medical

attention.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

**Ingestion:** Keep individual calm. Do not induce vomiting. Get medical attention.

### 5. FIRE FIGHTING MEASURES

Flash point: > 100.00 °C (> 212°F) Tagliabue closed cup

Autoignition temperature: Not available.

Flammable/Explosive limits - lower: 2 % (Acrylic Acid)

Flammable/Explosive limits - upper: 8 % (Acrylic Acid)

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Irritating organic vapours. Oxides of nitrogen. Oxides of sulfur. Oxides of

carbon.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand,

silica gel, acid binder, universal binder, sawdust). Store in a partly filled,

closed container until disposal.

## 7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous components                   | ACGIH TLV  | OSHA PEL                            | AIHA WEEL                             | OTHER                             |
|--|--|-------------------------------------|---------------------------------------|-----------------------------------|
| Polyurethane methacrylate resin        | None   | None                                | None                                  | None                              |
| Polyglycol dimethacrylate              | None   | None                                | None                                  | None                              |
| Silica, amorphous, fumed, crystal-free | 10 mg/m3 TWA<br>Inhalable dust.<br>3 mg/m3 TWA<br>Respirable fraction. | 20 MPPCF TWA<br>0.8 mg/m3 TWA       | None                                  | None                              |
| Acrylic acid                           | 2 ppm TWA<br>(SKIN)  | None                                | None                                  | 1 ppm TWA<br>3 ppm STEL<br>(SKIN) |
| Cumene hydroperoxide                   | None   | None                                | (SKIN)<br>1 ppm (6 mg/m3) None<br>TWA |                                   |
| Ethylene glycol                        | 100 mg/m3 Ceiling<br>Aerosol.  | None                                | None                                  | None                              |
| 1-Acetyl-2-phenylhydrazine             | None   | None                                | None                                  | None                              |
| Cumene                                 | 50 ppm TWA   | 50 ppm (245<br>mg/m3) TWA<br>(SKIN) | None                                  | None                              |

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). Use an organic vapor respirator for concentrations exceeding the

Occupational Exposure Limit.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Gel
Color: Red
Odor: Mild

Odor threshold:

pH:

Not available.

Not applicable

Vapor pressure:< 10 mm hg (80 °F (26.7 °C))</td>Boiling point/range:> 300 °F (> 148.9 °C) NoneMelting point/ range:Not available.Specific gravity:1.1 at 26.60 °C (79.88 °F)

Vapor density: Not available.

Flash point: > 100.00 °C (> 212°F) Tagliabue closed cup

Flammable/Explosive limits - lower:

Plammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

2 % (Acrylic Acid)

8 % (Acrylic Acid)

Not available.

Not available.

Slight

Partition coefficient (n-octanol/water): Not available.

**VOC content:** 1.77 %; 19.44 g/l (calculated)

# 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours. Phenolics.

Oxides of carbon.

Incompatible materials: Iron. Acids and bases. Rust. Reducing agents. Aluminum. Strong oxidizing

agents. Free radical initiators. Aldehydes. Oxygen scavengers. Strong alkalis.

Zinc. copper

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

# 11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 5,000 mg/kg (Estimated)

Acute dermal product toxicity: LD50 (rabbit) > 2,000 mg/kg

| Hazardous components                   | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen<br>(Specifically Regulated) |
|--|----------------|-----------------|---|
| Polyurethane methacrylate resin        | No             | No              | No  |
| Polyglycol dimethacrylate              | No             | No              | No  |
| Silica, amorphous, fumed, crystal-free | No             | No              | No  |
| Acrylic acid                           | No             | No              | No  |
| Cumene hydroperoxide                   | No             | No              | No  |
| Ethylene glycol                        | No             | No              | No  |
| 1-Acetyl-2-phenylhydrazine             | No             | No              | No  |
| Cumene                                 | No             | Group 2B        | No  |

| Hazardous components                   | Health Effects/Target Organs  |  |
|--|---|--|
| Polyurethane methacrylate resin        | Irritant, Allergen  |  |
| Polyglycol dimethacrylate              | Irritant, Allergen  |  |
| Silica, amorphous, fumed, crystal-free | Nuisance dust   |  |
| Acrylic acid                           | Allergen, Corrosive, Irritant, Kidney, Liver  |  |
| Cumene hydroperoxide                   | Allergen, Central nervous system, Corrosive, Irritant, Mutagen                                      |  |
| Ethylene glycol                        | Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic |  |
| 1-Acetyl-2-phenylhydrazine             | Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity                                  |  |
| Cumene                                 | Central nervous system, Irritant, Lung  |  |

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 135481

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:**Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312:

CERCLA/SARA 313:

Hydroquinone (CAS# 123-31-9). Delayed Health, Immediate Health

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Acrylic acid (CAS# 79-10-7). Cumene hydroperoxide (CAS# 80-15-9). Ethylene

glycol (CAS# 107-21-1).

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm. This product contains a chemical known in the State of California

to cause cancer.

## **Canada Regulatory Information**

WHMIS hazard class:

IDH number: 135481

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. D.2.A, D.2.B

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 9, 10

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.