Material Safety Data Sheet





Revision Number: 005.0 Issue date: 12/06/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE® 567™ PST® PIPE SEALANT IDH number: 234458

WITH h PTFE PTFE THREAD

SEALANT

Product type: Anaerobic Sealant Item number: 56765
Region: United States

Company address:Contact information:Henkel CorporationTelephone: 860.571.5100

One Henkel Way

MEDICAL EMERGENCY Phone: Poison Control Center
Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW HMIS:

 Physical state:
 Paste
 HEALTH:
 *2

 Color:
 White
 FLAMMABILITY:
 1

 Odor:
 Mild
 PHYSICAL HAZARD:
 1

Personal Protection: See MSDS Section 8

WARNING: CAUSES EYE IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation.

Skin contact: May cause skin irritation. May cause allergic skin reaction.

Eye contact: Contact with eyes will cause irritation. **Ingestion:** Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous components | CAS NUMBER | % |
|--|-------------|---------|
| Bisphenol A fumarate resin | 39382-25-7 | 30 - 60 |
| Polyglycol dimethacrylate | 25852-47-5 | 10 - 30 |
| Polyglycol laurate | 9004-81-3 | 10 - 30 |
| Polyethylene glycol monococoate | 61791-29-5 | 10 - 30 |
| Ethene, tetrafluoro-, homopolymer | 9002-84-0 | 5 - 10 |
| Titanium dioxide | 13463-67-7 | 1 - 5 |
| Silica, amorphous, fumed, crystal-free | 112945-52-5 | 1 - 5 |
| Saccharin | 81-07-2 | 1 - 5 |
| Epichlorohydrin-4,4'-isopropylidene diphenol resin | 25068-38-6 | 1 - 5 |
| Ethylene glycol | 107-21-1 | 0.1 - 1 |
| Cumene | 98-82-8 | 0.1 - 1 |

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Wash with soap and water.

Wash clothing before reuse. If symptoms develop and persist, get medical

attention.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point: > 93.3 °C (> 199.94 °F)

Autoignition temperature: Not available.

Flammable/Explosive limits - lower: Not available.

Flammable/Explosive limits - upper: Not available.

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Toxic fluorine

compounds. Irritating organic vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Store in a partly filled, closed container until

disposal.

IDH number: 234458 Product name: LOCTITE® 567™ PST® PIPE SEALANT WITH h PTFE PTFE THREAD SEALANT Page 2 of 6

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous components | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|--|--|-------------------------------------|-----------|---|
| Bisphenol A fumarate resin | None | None | None | None |
| Polyglycol dimethacrylate | None | None | None | None |
| Polyglycol laurate | None | None | None | None |
| Polyethylene glycol monococoate | None | None | None | None |
| Ethene, tetrafluoro-, homopolymer | None | None | None | 10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. |
| Titanium dioxide | 10 mg/m3 TWA | 15 mg/m3 TWA Total dust. | None | None |
| Silica, amorphous, fumed, crystal-free | 10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. | 20 MPPCF TWA 0.8 mg/m3 TWA | None | None |
| Saccharin | None | None | None | None |
| Epichlorohydrin-4,4'-isopropylidene diphenol resin | None | None | None | None |
| Ethylene glycol | 100 mg/m3 Ceiling Aerosol. | None | None | None |
| Cumene | 50 ppm TWA | 50 ppm (245 mg/m3) TWA (SKIN) | None | None |

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be

required if concentrations exceed occupational exposure limits.

Respiratory protection: Use a NIOSH approved supplied air respirator with an organic cartridge if the

potential to exceed established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Neoprene, Butyl-rubber, or nitrile-rubber gloves. Use impermeable gloves and

protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:PasteColor:WhiteOdor:MildOdor threshold:Not available.pH:Not applicable

 Vapor pressure:
 < 5 mm hg (27 °C (80.6 °F))</td>

 Boiling point/range:
 > 300 °F (> 148.9 °C) None

Melting point/ range:
Specific gravity:

Not available.
1.14

Vapor density: Not available.

Flash point: > 93.3 °C (> 199.94 °F)

Flammable/Explosive limits - lower: Not available.

Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Evaporation rate: Not available. Solubility in water: Slight Partition coefficient (n-octanol/water): Not available.

VOC content: 0.13 %; 1.38 g/l

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of nitrogen. Oxides of carbon. Oxides of sulfur. Toxic fluorine

compounds. Phenolics. Irritating organic vapours.

Incompatible materials: Free radical initiators. Amines. Aldehydes. Alkalis. copper Aluminum. Rust.

Bases. Acids. Strong oxidizing agents. Peroxides. Iron. Reducing agents.

Zinc.

Conditions to avoid: Heat, flames, sparks and other sources of ignition. See "Handling and

Storage" (Section 7) and "Incompatibility" (Section 10). Exposure to sunlight.

TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 10,000 mg/kg Acute dermal product toxicity: LD50 (rabbit) > 2,000 mg/kg

| Hazardous components | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|----------------|-----------------|--|
| Bisphenol A fumarate resin | No | No | No |
| Polyglycol dimethacrylate | No | No | No |
| Polyglycol laurate | No | No | No |
| Polyethylene glycol monococoate | No | No | No |
| Ethene, tetrafluoro-, homopolymer | No | No | No |
| Titanium dioxide | No | Group 2B | No |
| Silica, amorphous, fumed, crystal-free | No | No | No |
| Saccharin | No | No | No |
| Epichlorohydrin-4,4'-isopropylidene diphenol resin | No | No | No |
| Ethylene glycol | No | No | No |
| Cumene | No | Group 2B | No |

| Hazardous components | Health Effects/Target Organs | | |
|--|---|--|--|
| Bisphenol A fumarate resin | No Target Organs | | |
| Polyglycol dimethacrylate | Irritant, Allergen | | |
| Polyglycol laurate | Allergen, Irritant | | |
| Polyethylene glycol monococoate | No Target Organs | | |
| Ethene, tetrafluoro-, homopolymer | No Target Organs | | |
| Titanium dioxide | Irritant, Respiratory, Some evidence of carcinogenicity | | |
| Silica, amorphous, fumed, crystal-free | Nuisance dust | | |
| Saccharin | No Target Organs | | |
| Epichlorohydrin-4,4'-isopropylidene diphenol resin | Allergen, Irritant | | |
| Ethylene glycol | Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic | | |
| Cumene | Central nervous system, Irritant, Lung | | |

12. ECOLOGICAL INFORMATION

Ecological information: Do not empty into drains / surface water / ground water.

IDH number: 234458

Product name: LOCTITE® 567™ PST® PIPE SEALANT WITH h PTFE PTFE THREAD SEALANT

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA 313:

None above reporting de minimis
Immediate Health, Delayed Health
None above reporting de minimis

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm. This product contains a chemical known in the State of California

to cause cancer.

Canada Regulatory Information

WHMIS hazard class:

IDH number: 234458

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 3

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

Product name: LOCTITE® 567™ PST® PIPE SEALANT WITH h PTFE PTFE THREAD SEALANT

Page 5 of 6

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 234458