



Revision Number: 006.0

Issue date: 09/30/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE SF 790 GASKET REMOVER known as LOCTITE® Chisel® Paint Strippe	IDH number:	135544
Product type:	Cleaner	Item number:	79040
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CONTENTS UNDER PRESSURE.
EXTREMELY FLAMMABLE AEROSOL.
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
CAUSES SKIN IRRITATION.
CAUSES SERIOUS EYE DAMAGE.
MAY CAUSE DROWSINESS OR DIZZINESS.
SUSPECTED OF CAUSING CANCER.
MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	1
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2
ASPIRATION HAZARD	1

PICTOGRAM(S)



Precautionary Statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye and face protection. Wear protective gloves. Use personal protective equipment as required.

Response:

IF SWALLOWED: Immediately call a physician or poison control center. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. IF exposed or concerned: Get medical attention. Immediately call a poison control center or physician. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. Take off contaminated clothing.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

2 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Methanol	67-56-1	5 - 10
Flammable Propellant	Proprietary	10 - 30
Methylene chloride	75-09-2	60 - 100

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Seek medical advice.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call a physician immediately.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Firefighters should wear self-contained breathing apparatus. Water may be ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.
Unusual fire or explosion hazards:	Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Aerosol cans may rupture in heat or fire conditions.

Hazardous combustion products:

Irritating organic vapours. Phosgene. Hydrogen chloride. Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not allow to enter the ground / soil.

Clean-up methods:

Remove all sources of ignition. Spilled liquid is combustible and can be ignited by heat, flames, sparks, or other sources of ignition. Store in a closed container until ready for disposal. Soak up with inert absorbent. Scrape up spilled material and place in a closed container for disposal. For small spills wipe up with paper towel and place in container for disposal.

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid breathing mists or aerosols of this product.

Storage:

For safe storage, store between 0 °C (32°F) and 32 °C (89.6 °F)
Store in a cool, dry, well-ventilated area. Store in original container until ready to use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methanol	200 ppm TWA (SKIN) 250 ppm STEL	200 ppm (260 mg/m3) PEL	None	None
Flammable Propellant	None	None	None	None
Methylene chloride	50 ppm TWA	12.5 ppm OSHA_ACT 25 ppm TWA 125 ppm STEL	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Use only in well-ventilated areas.

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Silver Shield gloves. Viton gloves. Polyvinyl alcohol gloves. 4H gloves. EVAL-Laminate gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Aerosol, Liquid

Color:

Gray, to, Off white

Odor:

Sharp, Solvent

Odor threshold:

Not available.

pH:

Not available.

Vapor pressure:

Not available.

Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	0.789
Vapor density:	Not available.
Flash point:	< 5 °C (< 41°F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	Not available.
Solubility in water:	Slightly soluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	30 %; 237 g/l
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Hydrochloric acid. Oxides of carbon. Irritating organic vapours.
Incompatible materials:	Acids and bases. Oxidizing agents. Sodium. Potassium.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, spark and flame.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes
-------------------------------------	------------------------

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapor or aerosol may cause severe irritation to nose, throat and lungs. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.
Skin contact:	Causes skin irritation. May cause irritation due to defatting of the skin. Prolonged contact can cause reddening, swelling, rash, scaling, blistering and in some cases, skin sensitization.
Eye contact:	Causes serious eye damage.
Ingestion:	May be harmful or fatal if swallowed. May cause dizziness, incoordination, headache, nausea, and vomiting.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Methanol	Oral LD50 (RAT) = 5,628 mg/kg Oral LD50 (RABBIT) = 14.4 g/kg Dermal LD50 (RABBIT) = 15,800 mg/kg Inhalation LC50 (RAT, 6 h) = 87.5 mg/l Inhalation LC50 (RAT, 4 h) = 64000 ppm	Eyes, Heart, Irritant, Kidney, Liver, Metabolic, Nervous System, Reproductive
Flammable Propellant	None	No Records
Methylene chloride	Oral LD50 (RAT) = 1,600 mg/kg Oral LD50 (RAT) = 3,000 mg/kg Inhalation LC50 (RAT, 15 min) = 2,000 mg/l Inhalation LC50 (RAT, 2 h) = 79 mg/l Inhalation LC50 (RAT, 6 h) = 52 mg/l Inhalation LC50 (RAT, 900 d) = 88 mg/l	Blood, Cardiac, Central nervous system, Corrosive, Irritant, Kidney, Liver, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methanol	No	No	No
Flammable Propellant	No	No	No
Methylene chloride	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols, flammable
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Hazard class or division: 2.1 (6.1)
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name:	AEROSOLS (Methylene chloride)
Hazard class or division:	2.1 (6.1)
Identification number:	UN 1950
Packing group:	None

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health, Fire, Sudden Release
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methanol (CAS# 67-56-1). Methylene chloride (CAS# 75-09-2). Methylene chloride (CAS# 75-09-2) 1,000 lbs. (454 kg)
CERCLA Reportable quantity:	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Catherine Bimler, Regulatory Affairs Specialist

Issue date: 09/30/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.