

MATERIAL SAFETY DATA BULLETIN

mobil.com

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: MOBIL EAL ARCTIC 22BC

SUPPLIER: MOBIL OIL CORP.

NORTH AMERICA MARKETING AND REFINING

3225 GALLOWS RD.

FAIRFAX, VA 22037

24 - Hour Emergency (call collect): 609-737-4411

Product and MSDS Information:

800-662-4525

609-224-4644

CHEMIREC:

800-424-9300

202-483-7616

2. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAMES AND SYNONYMS: SYNTHETIC ESTERS AND ADDITIVES

INGREDIENTS CONSIDERED HAZARDOUS TO HEALTHS

This product is not formulated to contain ingredients which have exposure limits established by U.S. agencies. It is not hazardous to health as defined by the European Union Dangerous Substances/Preparations Directives. See Section 15 for a regulatory analysis of the ingredients.

See Section 15 for European Label Information.

See Section 8 for exposure limits (if applicable).

3. HAZARDS IDENTIFICATION

US OSHA HAZARD COMMUNICATION STANDARD: Product assessed in accordance with OSHA 29 CFR 1910.1200 and determined not to be hazardous.

EFFECTS OF OVEREXPOSURE: No significant effects expected.

EMERGENCY RESPONSE DATA: Straw Liquid. DOT ERG No. - NA. SEC: 0

4. FIRST AID MEASURES

EYE CONTACT: Flush thoroughly with water. If irritation occurs, call a physician.

SKIN CONTACT: Wash contact areas with soap and water.

INHALATION: Remove from further exposure. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with bag-valve-mask device or use mouth-to-mouth resuscitation.

(Section continued next page)

INGESTION: Not expected to be a problem. However, if greater than 1/2 liter (pint) ingested, immediately give 1 to 2 glasses of water and call a physician, hospital emergency room or poison control center for assistance. Do not induce vomiting or give anything by mouth to an unconscious person.

----- 5. FIRE-FIGHTING MEASURES -----

EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical and water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Water or foam may cause frothing.

Use water to keep fire exposed containers cool. Water spray may be used to flush spills away from exposure. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

SPECIAL PROTECTIVE EQUIPMENT: For fires in enclosed areas, fire fighters must use self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None. Flash Point C(F) : 230(446) (ASTM D-93). Flammable limits - LEL: NA, UEL: NA.

NFPA HAZARD ID: Health: 0, Flammability: 1, Reactivity: 0

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide-

----- 6. ACCIDENTAL RELEASE MEASURES -----

NOTIFICATION PROCEDURES: Report spills as required to appropriate authorities.. U. S. Coast Guard regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks. Report spill to Coast Guard toll free number (800) 424-8802. In case of accident or road spill notify CHEMTREC (800) 424-9300.

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED: Adsorb on fire retardant treated sawdust, diatomaceous earth, etc. Shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal.

ENVIRONMENTAL PRECAUTIONS: Prevent spills from entering storm sewers or drains and contact with soil-

PERSONAL PRECAUTIONS: See Section 8

----- 7. HANDLING AND STORAGE -----

HANDLING: This material is not intended for use in air compressors for breathing applications. No special precautions are necessary beyond normal good hygiene practices. See Section 3 for additional personal protection advice when handling this product.

STORAGE: Do not store in open or unlabelled containers. Store away from strong oxidizing agents or combustible material.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: Use in well ventilated area.

RESPIRATORY PROTECTION: No special requirements under ordinary conditions of use and with adequate ventilation.

EYE PROTECTION: Normal industrial eye protection practices should be employed.

SKIN PROTECTION: No special equipment required. However, good personal hygiene practices should always be followed,

EXPOSURE LIMITS: This product does not contain any components which have recognized exposure limits. However, a exposure limit of 5.00 mg/m³ is suggested for oil mist.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical. physical properties are given below. Consult Product Data Sheet for specific details.

APPEARANCE: Liquid

COLOR: Straw

ODOR: Mild

ODOR THRESHOLD-ppm: NE

pH: NA

BOILING POINT C(F) : > 316(600)

MELTING POINT C(F): NA

FLASH POINT C(F): 230(446) (ASTM D-93)

FLAMMABILITY: NE

AUTO FLAMMABILITY: NE

EXPLOSIVE PROPERTIES: NA

OXIDIZING PROPERTIES: NA

VAPOR PRESSURE-mmHg 20 C: < 0.1

VAPOR DENSITY: NE

EVAPORATION RATE: NE

RELATIVE DENSITY, 15/4 C: 0.99

SOLUBILITY IN WATER: Negligible

PARTITION COEFFICIENT: NE

VISCOSITY AT 40 C, cSt: 24.0

VISCOSITY AT 100 C, cSt: 4.9

POUR POINT C(F) : -54(-65)

FREEZING POINT C(F) : NE

VOLATILE ORGANIC COMPOUND: NA

NA=NOT APPLICABLE NE=NOT ESTABLISHED D=DECOMPOSES

FOR FURTHER TECHNICAL INFORMATION, CONTACT YOUR MARKETING REPRESENTATIVE

10. STABILITY AND REACTIVITY

STABILITY (THERMAL, LIGHT, ETC.) : Stable.

CONDITIONS TO AVOID: Extreme heat.

INCOMPATIBILITY (MATERIALS TO AVOID): strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL DATA

---ACUTE TOXICOLOGY---

ORAL TOXICITY (RATS): Practically non-toxic (LD50: greater than 2000 mg/kg). ---Based on testing of similar products and/or the components.

DERMAL TOXICITY (RABBITS): Practically non-toxic (LD50: greater than 2000 mg/kg). ---Based on testing of similar products and/or the components.

INHALATION TOXICITY (RATS): Not established

EYE IRRITATION (RABBITS): Practically non-irritating. (Draize score: greater than 6 but 15 or less). ---Based on testing of similar products and/or the components.

SKIN IRRITATION (RABBITS): Practically non-irritating. Primary Irritation Index: greater than 0.5 but less than 3). ---Based on testing of similar products and/or the components.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND EFFECTS: This material is biodegraded to greater than 95% in 21 days by the CEC L-33-A-93 Test; 70% of this material is converted to CO2 in 28 days (EPA Shake Flask Test).

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. In-addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

RCRA INFORMATION: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

14. TRANSPORT INFORMATION

USA DOT: NOT REGULATED BY USA DOT.

RID/ADR: NOT REGULATED BY RID/ADR.

IMO: NOT REGULATED BY IMO.

IATA: NOT REGULATED BY IATA.

15. REGULATORY INFORMATION
-----Governmental Inventory Status: All components comply with TSCA,
EINECS/ELINCS, AICS, and DSL.

EU Labeling: EU labeling not required.

U.S. Superfund Amendments and Reauthorization Act (SARA) Title III:
This product contains no "EXTREMELY HAZARDOUS SUBSTANCES".

SARA (311/312) REPORTABLE HAZARD CATEGORIES: None.

This product contains no chemicals reportable under
SARA (313) toxic release program.

The following product ingredients are cited on the lists below:

CHEMICAL NAME	CAS NUMBER	LIST CITATIONS
-----	-----	-----
TRICRESYL PHOSPHATE (0.50%)	1330-78-5	22

--- REGULATORY LISTS SEARCHED ---

1=ACGIH ALL	6=IARC 1	11=TSCA 4	16=CA P65 CARC	21=LA RTK
2=ACGIH A1	7=IARC 2A	12=TSCA 5a2	17=CA P65 REPRO	22=MI 293
3=ACGIH A2	8=IARC 2B	13=TSCA 5e	18=CA RTK	23=MN RTK
4=NTP CARC	9=OSHA CARC	14=TSCA 6	19=FL RTK	24=NJ RTK
5=NTP SUS	10=OSHA z	15=TSCA 12b	20=IL RTK	25=PA RTK
				26=RI RTK

Code key: CARC=Carcinogen; SUS=Suspected Carcinogen; REPRO=Reproductive

16. OTHER INFORMATION

USE: COMPRESSOR OIL

NOTE: MOBIL PRODUCTS ARE NOT FORMULATED TO CONTAIN PCBS.

INGREDIENT

CAS NUMBER

<----->
COMPRESSOR OIL<----->
NJTS 003066009-5119*****
For Internal Use Only: MHC: 1* 1* NE 1* 1*, MPPEC: A, TRN:
6017735-00, REQ: EDISON/CPD, SAFE USE: L
EHS Approval Date: 03APR1998

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL, WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. Mobil assumes no responsibility for accuracy of information unless the document is the most current available from an official Mobil distribution system. Mobil neither represents nor warrants that the format, content or product formulas contained in this document comply with the laws of any other country except the United States of America.

Copyright 1996 Mobil Corporation, All rights reserved