

A CSW Industrials Company

SAFETY <u>DATA SHEET</u>

ODORGON™ SPRAY

Fuel Oil Neutralizer

SECTION 1 - PRODUCT AND COMPANY INFORMATION

Product name Odorgon Spray

Product Codes 68516 Chemical Family Organic/Inorganic Use

Fuel Oil Deodorizer Manufacturer's Name RectorSeal LLC 2601 Spenwick Drive Houston, Texas 77055 USA

Date of validation December 4,2019

Date of Preparation December 4, 2019 HMIS Codes

Health 2

Flammability 3

Reactivity 0

PPI B

Emergency Telephone No. Chemtrec 24 Hours (800) 424-9300 USA (703) 527-3887 International

Technical Service Telephone No. (800) 231-3345 or (713) 263-8001

Section 2 - Hazards Identification

EMERGENCY OVERVIEW

OSHA Physical Hazards Flamable Aerosol (Category 2)

GHS CLASSIFICATION

Acute toxicity, Oral, Not Classified

Dermal: Not Classified Inhalation: Not Classified

Skin Corrosion/Irritation: (Category 2)

Serious Eye Damage/Eye Irritation: (Category 2B) Respiratory or Skin Sensitization: Not Classified

Germ Cell Mutagenicity: Not Classified

Carcinogenicity: Not Classified

Reproductive Toxicology: Not Classified

Target Organ Systemic Toxicity - Single Exposure: Not Classified Target Organ Systemic Toxicity - Repeated Exposure: Not Classified

Aspiration Toxicity: Not Classified

Specific target organ toxicity - single exposure (Category 3), Central nervous system

Page 1 of 8 R50490-1020

ODORGON™ SPRAY

Fuel Oil Neutralizer

GHS Label elements, including precautionary statements





Signal Word: Warning GHS04: Gas Cylinder GHS07: Exclamation Mark

Hazard Statements:

H303 - May be harmful if swallowed.

H313 - May be harmful in contact with skin.

H320 - Causes eye irritation

H335 + H336 - May cause respiratory irritation, and drowsiness or dizziness.

H280 - Contains gas under pressure; may explode if heated.

Precautionary Statements:

Prevention

P102 - Keep out of reach of children.

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P211 - Do not spray on an open flame or other ignition source.

P251 - Pressurized container; do not pierce or burn, even after use.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P262 - Do not get in eyes, on skin, or on clothing.

P264 - Wash skin thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P332 + P313 - If skin irritation occurs: Get medical advice/ attention.

P337+313 - If eye irritation persists get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410 + 412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant.

SUMMARY OF ACUTE HAZARDS

Irritation to eyes, nose, and throat; drowsiness, narcosis, tremors, and other CNS effects at high concentrations. Skin irritation, dermatitis, and defatting.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

Page 2 of 8 R50490-1020

ODORGON™ SPRAY

Fuel Oil Neutralizer

INHALATION

Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression, and unconsciousness.

EYE CONTACT

Watering, blurred vision, inflammation, and irritation which can result in corneal injury.

SKIN CONTACT

Irritation, dermatitis

INGESTION

Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion. SUMMARY OF CHRONIC HAZARDS

Skin irritation, contact dermatitis, and defatting.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

Section 3 - Composition/Information on Ingredients

Ingredient: Hexylene Glycol

Percentage by weight: 1-10

CAS#: 107-41-5 EINEC#: 203-489-0

Ingredient: Isopropyl Alcohol

Percentage by weight: 1-10

CAS#: 67-63-0 EINEC#: 200-661-7

Ingredient: Polyethylene glycol octylphenyl ether (Surfactant)

Percentage by weight: 1-5

CAS#: 9036-19-5

EINEC#:

Ingredient: Methyl Salicylate

Percentage by weight: 1-5

CAS#: 119-36-8 EINEC#: 204-317-7

Ingredient: Water

Percentage by weight 70-80

CAS#: 7732-18-5

EINEC#: 231-791-2

Page 3 of 8 R50490-1020

SECTION 4 - FIRST AID MEASURES

If INHALED If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial

respiration as needed. Obtain emergency medical attention. Prompt action is essential.

If on SKIN Immediately wash with soap and water. Remove and wash any contaminated clothing.

If in EYES Flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

If SWALLOWED If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician.

Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

EXTINGUSING MEDIA

Foam, dry chemical, CO2, or water fog.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear self-contained full face piece breathing apparatus and full body protective clothing. Hazardous decomposition products possible (see Section 10). Evacuate area. Dike area as run-off may create additional environmental contamination.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Aerosol cans are under pressure - exposure to temperatures above 120 F can cause bursting or "rocketing" of cans.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Shake well before using. Keep away from heat, sparks and open flames. Prolonged exposure to direct sunshine or storage above 120 F may cause can to burst. Do not puncture or incinerate can.

OTHER PRECAUTIONS:

Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers.

Page 4 of 8 R50490-1020

Section 8 - Exposure Controls/Personal Protection

Ingredient Units

Hexylene Glycol

ACGIH TLV 25 ppm OSHA PEL 25 ppm

Isopropyl Alcohol

 ACGIH TLV
 400 ppm

 OSHA PEL
 400 ppm

 OSHA STEL
 500 ppm

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirators during soldering operations until fumes have dissipated.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: Explosion proof

MECHANICAL (GENERAL): Acceptable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent),

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Chemical resistant coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: N/D

Specific Gravity ($H_20 = 1$): 0.98 Vapor Pressure (mm Hg): N/D

Melting Point: N/A

Vapor Density (Air = 1): <1

Evaporation Rate (Ethyl Acetate = 1): >1

Appearance/Odor: Clear Liquid / Fragrant Odor

Solubility In Water: Soluble

Flash Point: 53 F (12 C) SETA CC

2.5

Aerosol Flame Extension: Negative

VOLATILE ORGANIC COMPOUNDS (VOC)

Content (Theoretical Percentage By Weight): 19% or (186 g/L)

NFPA AEROSOL LEVEL: LOWER EXPLOSION LIMIT:

UPPER EXPLOSION LIMIT: 12

Page 5 of 8 R50490-1020



SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: Do not store in temperatures above 120 F. **Incompatibility (Materials to Avoid):** Oxidizers, acids and bases.

Hazardous Decomposition Products: CO, CO, and fragmented hydrocarbons.

Hazardous Polymerization: Will not occur.

SECTION 11 - TOXICOLOGY INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Toxicology Data

Ingredient Name

Hexylene Glycol

Oral-Rat adult LD50: 3700 mg/kg Inhalation-Rat LC50: N/D

Isopropyl Alcohol

Oral-Rabbit, adult LD50: 5045 mg/kg Inhalation-Rat LCLo: 16,000 ppm 4H

SECTION 12 - ECOLOGICAL INFORMATION

Ecological Data

Ingredient Name

Hexylene Glycol

Food Chain Concentration Potential None WATERFOWL TOXICITY N/A BOD N/A AQUATIC TOXICITY N/A

Isopropyl Alchohol

Food Chain Concentration Potential None WATERFOWL TOXICITY N/A

BOD 133%, 5 days

AQUATIC TOXICITY 900-1100 ppm/24 hr/chub/critical range

Page 6 of 8 R50490-1020



SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Classification: Aerosols

Disposal Method: Empty containers can be disposed of in trash. Full containers should be depressurized to separate liquid phase. The liquid phase is considered a D001 ignitable waste and should be incinerated. Dispose of all liquid waste in accordance with all local, state and federal regulations.

SECTION 14 - TRANSPORTATION INFORMATION

DOT: Limited Quantity or (LTD-QTY)

OCEAN (IMDG): UN1950, Aerosols, 2.2, Ltd Qty or Limited Quantity, EmS No. F-D, S-U

AIR (IATA): UN1950, Aerosols, 2.2, ERG#126

Section 15 - Regulatory Information

Regulatory Data Ingredient Name

Hexylene Glycol

SARA 313 No
TSCA Inventory Yes
CERCLA RQ N/A
RCRA Code N/A

Isopropyl Alcohol

SARA 313 Yes
TSCA Inventory Yes
CERCLA RQ N/A
RCRA Code N/A

SECTION 16 - OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001

Page 7 of 8 R50490-1020