CB15 & CB20



Beckett's family of medium condensate pumps are designed to meet or exceed your toughest job demands, including high efficiency gas furnaces. This pump is engineered to be user friendly with features like lift-to-test-tab for the main switch and the ability to mount the pump from either side. It features a larger replaceable Duck-Bill check valve design and convenient discharge with both 3/8" O.D. barb and 1/4" MNPT threads.





Model #	Н	W	ι	Outlet	Inlet	Volts	Amps	Watts	Gallons per hour @ 60Hz/ Rated Voltage					Check	6 Ft. Cord	Tubing	6 Ft. Cord	Shut Off	Weight Lb.
									1'	5′	10'	15'	Switch	Valve	w/plug	rubing	w/plug	(Ft.)	Each
CB151UL	6 1/2"	5"	11 1/4"	3/8" O.D.	1.1"	115	0.9	53	125	103	66	-	V	√	√		V	18′	3.9
CB151LSUL	6 1/2"	5"	11 1/4"	3/8" O.D.	1.1"	115	0.9	53	125	103	66	-		V	√		V	18′	3.9
CB151TUL	6 1/2"	5"	11 1/4"	3/8" O.D.	1.1"	115	0.9	53	125	103	66	-	V	V	V	V	V	18′	4.9
CB201UL	6 1/2"	5"	11 1/4"	3/8" O.D.	1.1"	115	1.1	60	115	72	51	20	V	V	√		V	20′	4.4
CB201LSUL	6 1/2"	5"	11 1/4"	3/8" O.D.	1.1"	115	1.1	60	115	72	51	20		V	√		V	20′	4.4
CB201TUL	6 1/2"	5"	11 1/4"	3/8" O.D.	1.1"	115	1.1	60	115	72	51	20	V	V	√	√	V	20′	5.4
CB202TUL	6 1/2"	5"	11 1/4"	3/8" O.D.	1.1"	230	1.1	89	140	118	84	39	V	V	√	V	V	20′	5.4
CB202UL	6 1/2"	5"	11 1/4"	3/8" O.D.	1.1"	230	1.1	89	140	118	84	39	V	V	V		V	20′	4.4

Beckett Automatic Condensate Units Coding Legend:

1- 115V 2-230V

T- Tubing Included (20 ft. of 3/8 in. I.D.)

LS- Less Safety Switch

UL- Standard Unit 150°F Max. Water Temp.

Tank Capacity:

CB15, CB20...... 2.0 US quart (1.9 Liters)

Average Performance