

MATERIAL SAFETY DATA SHEET- ESP PART NUMBER 757WC

REVISION DATE: 10-08-2003

SUPERSEDES: 07-11-1999

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY INFORMATION

ESP Company 27 S. Perry Street Vandalia, OH 45377 Phone: 937-898-0391

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION

PRODUCT IDENTIFIER:

804812PM

PRODUCT NUMBER:

SC0288 773

PRODUCT NAME:

757W WHITE

PRODUCT DESCRIPTION:

Caulk

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for any additional exposure limit guidelines.

Chemical Name	CAS#	PERCENT	OSHA PEL
Calcium carbonate	1317-65-3	30 -50	TWA (Total dust) 15 MG/M3
			TWA (Respirable dust) 5MG/M3
Stoddard solvent	8052-41-3	10 -30	TWA 100 ppm
Tremolite			
(non-asbestiform)	14567-73-8	1 -5	Not established
Talc	14807-96-6	1 -5	TWA (Respirable dust) 2 MG/M3
Titanium dioxide	13463-67-7	1 -5	TWA (Total dust) 10 MG/M3
Crystalline silica	14808-60-7	0.1 -1	TWA (Respirable dust) 0.1MG/M3

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Combustible
Moderate eye irritant.
Can cause skin irritation.
Harmful if swallowed.
Cancer hazard.

HMIS RATING: HEALTH --1 FLAMMABILITY --2 REACTIVITY --0 See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue. SKIN: Can cause skin irritation.

Component(s) may be absorbed through intact skin, but it is unlikely that harmful effects will occur unless contact is

prolonged, repeated, and extensive.

INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract. Inhalation of high concentrations may result in central nervous system (CNS) effects such as dizziness, weakness, fatigue, nausea, headache, and lack of coordination. Overexposure to crystalline silica may cause silicosis.

INGESTION: Ingestion is not an anticipated route of exposure. Harmful if swallowed. Irritating to mouth, throat, and stomach.

LONG-TERM (CHRONIC) HEALTH EFFECTS
TARGET ORGAN(S): Kidneys Central nervous system Lungs

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Crystalline silica

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Kidney disease: Lung disease

SECTION 4: FIRST AID MEASURES

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention immediately. Drink two glasses of warm milk to dilute. Do not give anything by mouth to an unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT:

43C; 109F

AUTOIGNITION TEMPERATURE:

Not established

UPPER EXPLOSIVE LIMIT (% in air):

Not established

EXTINGUISHING MEDIA:

Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and can travel to a source of

ignition and flash back.

SPECIAL FIRE FIGHTING INSTRUCTIONS:

Persons exposed to products of combustion should wear

self-contained breathing apparatus and full protective

equipment.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon dioxide, Carbon monoxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION:

No health effects expected from the cleanup of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

CLEAN-UP:

Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Mildly irritating material. Avoid unnecessary exposure.

Keep away from heat, sparks and flame.

Wash thoroughly after handling.

Keep container closed.

Emptied container retains vapor and product residue.

Observe all labeled precautions until container is cleaned.

Drums of this material should be grounded when pouring.

DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Storage: Store in a cool, dry, ventilated location. Keep away from heat and flame.

Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear safety glasses with side shields when handling this product.

Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

station available.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves.

GLOVES: Nitrile

RESPIRATORY

PROTECTION: Respiratory protection may be required to avoid overexposure when

handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved

air purifying respirator with organic vapor cartridge.

Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimize exposures.

EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	AIHA WEEL
Calcium carbonate	TWA (Total dust) 10 MG/M3	Not established
Stoddard solvent	TWA 100 ppm	Not established
Tramalita (non ashastifarm)	Not established	Not established
Tremolite (non-asbestiform)	Not established	Not established
Talc	TWA (Respirable dust) 2 MG/M3	Not established
Titanium dioxide	TWA (Total dust) 10 MG/M3	Not established
Crystalline silica	TWA (Respirable dust) 0.05 MG/M3	Not established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:

Semi-solid

COLOR:

White

ODOR:

Solvent

ODOR THRESHOLD:

Not established

SPECIFIC GRAVITY:

10.63 1.28

SOLIDS (% by weight):

79.0 Not established

pH: BOILING POINT (deg. C):

Not established

FREEZING/MELTING POINT (deg. C):

WEIGHT PER GALLON (lbs.):

Not established

VAPOR PRESSURE (mm Hg):

Not established

VAPOR DENSITY:

Not established

EVAPORATION RATE:

Not established

OCTANOL/WATER COEFFICIENT:

Not established

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

Stable under normal conditions.

CHEMICAL INCOMPATIBILITY:

Strong oxidizing agents

HAZARDOUS POLYMERIZATION:

Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

CHEMICAL NAME	LD50/LC50		
Calcium carbonate	Oral LD50 Rat = 6250 mg/kg		
Stoddard solvent	Not established		
Tremolite (non-asbestiform)	Not established		
Talc	Not established		
Titanium dioxide	Not established		
Crystalline silica	Not established		

TOXICOLOGY SUMMARY: No additional health information available.

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

268.00 g VOC/liter of material

(VOC theoretically determined using EPA Publication 450/3-84-019)

268.00 g VOC/liter of material, less water and exempt solvents

(VOC theoretically determined using EPA Publication 450/3-84-019.)

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

DOT:

ADHESIVES,3,UN1133,PG.III

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: This product is in compliance with the Canadian Domestic Substance List

requirements.

If you need more information about the inventory status of this product call 651-236-5858.

TSCA Section 12(b) -Export Notice Requirements

This product contains a chemical substance that is currently on the EPA's Section 12(b) Export List. Contact the company Global Regulatory Group at 651/236-5858 for the identity of the Section 12(b) chemical(s).

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 72. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name

CAS#

%

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

B3

D2B D2A

STATE REPORTING

This MSDS is not prepared for distribution in California.

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to EFTEC North America, L.L.C. from its suppliers, and because EFTEC North America, L.L.C. has no control over the conditions of handling and use, EFTEC North America, L.L.C. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and EFTEC North America, L.L.C. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of EFTEC North America, L.L.C. products to comply with all applicable federal, state and local laws and regulation.