

DURO DYNE CORPORATION  
81 SPENCE STREET  
BAY SHORE, N.Y. 11706  
EMERGENCY PHONE NO. 800-424-9300 (CHEMTREC)  
INFORMATION PHONE NO. 800-899-3876

H.M.I.S.	
HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	See Below
These ratings should be used only as part of fully implemented H.M.I.S. program.	

# MATERIAL SAFETY DATA SHEET

PREPARED BY DURO DYNE 6/2005  
REVISED 6/2000

## SECTION I

TRADE NAME: DURO DYNE SILICONIZED ACRYLIC DUCT SEALER  
MANUFACTURER CODE I.D.: SAS

## SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS #	PERCENT	OSHA PEL PPM	ACGIH TLV	OSHA, ACGIH STEL PPM	SARA	VP mmHg @20°C
MINERAL SPIRITS	64742-88-7	1.07	500	100			
CALCIUM CARBONATE**	1317-65-3	>60.0	15	10			
ETHYLENE GLYCOL***		.90	50	50			
BENZOATE ESTER	27138-31-4	>6					
BIS (TRIBUTYL TIN) OXIDE***	56-35-9	<.05					
OCTYLPHENOL ETHOXYLATE	9036-19-5						

\*\* Inhalation of particulates unlikely due to product's physical state.

\*\*\* Combustible material. Store in a closed container in a cool area. This product contains bis (tributyltin) oxide and the minimum value of ethylene glycol, ingredients listed in Section 313 of SARA Title III and 40 CFR 372.65.

## SECTION III - FIRST AID AND EMERGENCY MEASURES

**EFFECTS OF OVEREXPOSURE:** Inhalation of dust generated from dried product may cause respiratory irritation. High vapor concentrations may produce headache, dizziness, and nausea. Prolonged or repeated contact may cause mild skin and eye irritation.

**EYES:** Flush immediately with large amounts of water while holding the eyelids open. Get medical attention if irritation persists.

**SKIN:** Wipe material from skin with cloth or paper towel, then wash exposed area with soap and water. Get medical help if irritation persists.

**INHALATION:** Remove subject to fresh air and treat symptomatically.

**INGESTION:** Contact local poison control center or physician IMMEDIATELY!

## SECTION IV - PROTECTION INFORMATION

**EYES:** Wear safety glasses.

**SKIN:** In situations of extended skin contact, neoprene, or other chemical resistant gloves are recommended.

**INHALATION:** Not normally required. If TLV is exceeded, or for symptoms of overexposure, wear a NIOSH approved respirator for organic vapors.

**VENTILATION:** Provide adequate general dilution ventilation.

## SECTION V - PHYSICAL DATA

PHYSICAL STATE: Paste  
COLOR: White  
ODOR: Mild acrylic  
VAPOR PRESSURE: N.E.  
VAPOR DENSITY: >1

PH: 7.5 - 8.0  
SOLUBILITY IN WATER: Appreciable  
FREEZING/MELTING POINT: N.E.  
EVAPORATION RATE: >1 (BuAc=1)  
SPECIFIC GRAVITY: 1.5 - 1.75

## SECTION VI - FIRE AND EXPLOSION DATA

FLASH POINT: 150°  
U.E.L./ L.E.L.: N.E.  
EXTINGUISHERS: Carbon Dioxide, Dry Chemical, or Foam.  
SPECIAL FIRE FIGHTING PROCEDURES: Use water spray or fog to cool fire-exposed containers.

## SECTION VII - REACTIVITY DATA

STABILITY: Stable. Avoid extreme heat, open flame.  
INCOMPATIBLE MATERIALS: Strong oxidizers.  
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide

## SECTION VIII - HANDLING PROCEDURES

HANDLING: Clean up with absorbent material. Dispose of in accordance with Local, State, and Federal Regulations.

THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE BELIEVED TO BE ACCURATE. BECAUSE SOME OF THE INFORMATION IS PROVIDED TO DURO DYNE CORPORATION FROM ITS SUPPLIERS, DURO DYNE CORPORATION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SINCE THE USE OF THIS INFORMATION AND THE CONDITIONS AND USE OF THIS PRODUCT ARE CONTROLLED BY THE USER, IT IS THE USER'S OBLIGATION TO DETERMINE THE CONDITIONS OF SAFE USE OF THE PRODUCTS. THE INFORMATION IS SUPPLIED SOLELY FOR YOUR INFORMATION AND CONSIDERATION AND DURO DYNE CORPORATION ASSUMES NO RESPONSIBILITY FOR USE OR RELIANCE THEREON. IT IS THE RESPONSIBILITY OF THE USER OF DURO DYNE CORPORATION PRODUCTS TO COMPLY WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.