

MATERIAL SAFETY DATA SHEET

MSDS Name: KINGCO 15-156 DUCT LINER ADHESIVE
 MSDS Number: 15-156

MSDS Last Updated: NOV-18-2002 Printed On: 11/19/02
 Page Number: 1 of 6

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: KINGCO 15-156 DUCT LINER ADHESIVE
 CAS Number: MIXTURE
 Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPI: G

Company Identification: ITW TACC
 AIR STATION INDUSTRIAL PARK
 ROCKLAND MA 02370

Telephone/Fax: (781) 878-7015 (781) 871-6727
 Chemtrec (24 Hour): (800) 424-9300

Trade Name: KINGCO 15-156
 Product Code: 15-156
 DOT Hazard Class: 3
 UN Number: 1133
 Shipping Name: ADHESIVES
 Packing Group: II

SECTION II - HAZARDOUS INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
LIGHT ALIPHATIC NAPHTHA	64742-89-8	15-40	Y
HEXANE	110-54-3	10-30	Y
CYCLOHEXANE	110-82-7	1-5	Y
CHLORINATED PARAFFIN RESIN	63449-39-8	1-5	Y
ANTIMONY TRIOXIDE	1309-64-4	< 0.5	Y

SECTION III - PHYSICAL DATA

Appearance/Color: BLACK
 Boiling Range: 156.0F

MATERIAL SAFETY DATA SHEET

MSDS Name: KINGCO 15-156 DUCT LINER ADHESIVE
MSDS Number: 15-156

MSDS Last Updated: NOV-18-2002 Printed On: 11/19/02
Page Number: 2 of 6

Evaporation Rate: Faster than n-Butyl Acetate
% Volatile Weight: 65.41%
% Volatile Volume: Not Available
Specific Gravity: 0.792
Weight/Volume Measure: 6.59500
EPA Method 24 VOC: 499.8 g/L

Photo Chem Reactive Only VOC: 499.8

=====
SECTION IV - FIRE AND EXPLOSION HAZARD DANGER
=====

Flammability Class: IB
Flash Range: 0 F
Tag Closed Cup
Explosive Range: 1.0%
7.5%

EXTINGUISHING MEDIA:

Foam, dry chemical, carbon dioxide, water spray or fog.

SPECIAL FIREFIGHTING PROCEDURES:

Wear a self-contained breathing apparatus.

UNUSUAL FIRE & EXPLOSION HAZARDS:

Vapors are heavier than air and may travel to an ignition source distant from the material handling point.

=====
SECTION V - HEALTH HAZARD DATA
=====

PERMISSIBLE EXPOSURE LEVEL:

SEE SECTION VIII.

EFFECTS OF OVEREXPOSURE:

INGESTION: Can cause gastrointestinal irritation, nausea and vomiting. Aspiration of material into lungs may cause chemical pneumonitis which can be fatal.

INHALATION: May cause nose or throat irritation. High concentrations may cause acute central nervous system depression characterized by headaches, dizziness, nausea and confusion.

EYES: May cause severe eye irritation and corneal damage.

SKIN: May cause dermatitis. May cause defatting and irritation of the skin.

FIRST AID:

EYES: Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention.

MATERIAL SAFETY DATA SHEET

MSDS Name: KINGCO 15-156 DUCT LINER ADHESIVE
MSDS Number: 15-156

MSDS Last Updated: NOV-18-2002 Printed On: 11/19/02
Page Number: 3 of 6

SKIN: Prolonged or repeated contact can cause irritation and possible defatting of skin.
INGESTION: Do not induce vomiting, keep person warm, quiet, and get medical attention (aspiration of this material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.
INHALATION: Remove individual to fresh air and if breathing is difficult, administer oxygen.

=====

SECTION VI - REACTIVITY DATA

=====

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY:
Strong oxidizing agents, strong acids and bases.
CONDITIONS TO AVOID:
Fire, sparks, static electricity.
HAZARDOUS DECOMPOSITION PRODUCTS:
Carbon monoxide, carbon dioxide.

=====

SECTION VII - SPILL OR LEAK PROCEDURES

=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Keep spectators away. Eliminate all ignition sources (flames, hot surfaces and sources of electrical, static or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams and groundwater with spilled material or used absorbent.
WASTE DISPOSAL METHOD:
Dispose of in accordance with federal, state and local regulations.

=====

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

=====

Occupational Exposure Limits:

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

LIGHT ALIPHATIC NAPHTHA

MATERIAL SAFETY DATA SHEET

MSDS Name: KINGCO 15-156 DUCT LINER ADHESIVE
MSDS Number: 15-156

MSDS Last Updated: NOV-18-2002 Printed On: 11/19/02
Page Number: 4 of 6

	100.00 PPM	N/est	N/est	N/est	500.00 PPM
HEXANE	400.00 PPM	N/est	500.00 PPM	N/est	500.00 PPM
CYCLOHEXANE	200.00 PPM	N/est	N/est	N/est	200.00 PPM
CHLORINATED PARAFFIN RESIN	N/est	N/est	N/est	N/est	N/est
ANTIMONY TRIOXIDE	0.50 mg/M3	N/est	N/est	N/est	0.50 mg/M3

RESPIRATORY PROTECTION:

If workplace exposure limit of product is exceeded, a NIOSH/MSHA approved air supplied respirator must be used in absence of proper environmental control. Engineering or administrative controls should be implemented to reduce exposure.

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL.

PROTECTIVE GLOVES:

Chemical resistant gloves.

EYE PROTECTION:

Chemical splash goggles in compliance with OSHA regulations are advised.

OTHER PROTECTIVE EQUIPMENT:

To prevent repeated, prolonged skin contact, wear impervious clothing and boots.

=====
SECTION IX - SPECIAL PRECAUTIONS
=====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container closed when not in use. Store at 60-95 degrees F and out of the sun. Use adequate ventilation to avoid breathing vapors when cover is removed. Ground all equipment when handling flammable solventborne materials.

OTHER PRECAUTIONS:

For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe fumes. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Close all containers when not in use.

MATERIAL SAFETY DATA SHEET

MSDS Name: KINGCO 15-156 DUCT LINER ADHESIVE
MSDS Number: 15-156

MSDS Last Updated: NOV-18-2002 Printed On: 11/19/02
Page Number: 5 of 6

Empty containers must not be washed and re-used for any purpose.
Contact lens wearers take appropriate precautions. Wash hands
thoroughly after handling.

For spray applications, use only with approved spray equipment.

For flammable products, vapors may cause flash fire or ignite
explosively. To prevent buildup of vapors, use adequate ventilations
(e.g. open all windows and doors to achieve cross-ventilation).
Containers may be hazardous when empty. Never use welding or cutting
torch on or near container.

=====
SECTION X - ADDITIONAL REGULATORY INFORMATION
=====

-SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the
reporting requirements of Section 313 of the Emergency Planning and
Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
HEXANE	110-54-3	10-30
CYCLOHEXANE	110-82-7	1-5

-PROP 65 (CARCINOGEN)

WARNING: This product contains a chemical known to the state of
California to cause cancer.

Ingredient Name	CAS Number	Percent
ANTIMONY TRIOXIDE	1309-64-4	< 0.5

The following ingredients are registered for TSCA 12B

Ingredient Name	CAS Number	Percent
HEXANE	110-54-3	10-30
CYCLOHEXANE	110-82-7	1-5
ANTIMONY TRIOXIDE	1309-64-4	< 0.5

=====
DISCLAIMER
=====

MATERIAL SAFETY DATA SHEET

MSDS Name: KINGCO 15-156 DUCT LINER ADHESIVE

MSDS Number: 15-156

MSDS Last Updated: NOV-18-2002

Printed On: 11/19/02

Page Number: 6 of 6

***** NOTICE *****

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW TACC. The data on this sheet relates only to the specific material designated herein. ITW TACC assumes no legal responsibility for use or reliance upon these data.
